



SLIKA	OPIS
2MP HDCVI KAMERE	
	<p>Model: HAC-T1A21-0360/0280B Cooper 1/2.7" CMOS 2mpx cip, 1080P (1920×1080), 2MP domet dioda do 20m; fixna optika, vidni ugao 3.6mm- 93°/2.8mm - 103°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR: DWDR, Max 2.7W (12V DC, IR on), Kuciste: plasticno. Dozna PFA135, Nosac PFA152-E.</p>
	<p>Model: HAC-B1A21-0360B Cooper 1/2.7" CMOS 2mpx cip, 1080P (1920×1080), 2MP domet dioda do 20m; fixna optika, vidni ugao 3.6mm- 93°/2.8mm - 103°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR: DWDR, Max 2.7W (12V DC, IR on), Kuciste: plasticno. Dozna PFA134, Nosac PFA152-E.</p>
	<p>Model: HAC-T2A21-0360/0280B Cooper 1/2.7" CMOS 2mpx cip, 1080P (1920×1080), 2MP domet dioda do 20m; fixna optika, vidni ugao 3.6mm- 93°/2.8mm - 103°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR: DWDR, Max 2.7W (12V DC, IR on), Kuciste: metalno. Dozna PFA130-E, Nosac PFA152-E.</p>
	<p>Model: HAC-B2A21-0360B Cooper 1/2.7" CMOS 2mpx cip, 1080P (1920×1080), 2MP domet dioda do 20m; fixna optika, vidni ugao 3.6mm- 93°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR: DWDR, Max 2.7W (12V DC, IR on), Kuciste: metalno. Dozna PFA130-E, Nosac PFA152-E.</p>



Model: **HAC-HDW1200TRQ-0280B**

1/2.7" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 2, domet dioda do 25m; fixna optika, vidni ugao/ 2.8mm - 103°,
Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR: DWDR, Max
3.3W (12V DC, IR on), Kuciste: plasticno.IP50 Zastita
Dozna PFA130-E, Dozna PFA13G.



Model: **HAC-HFW1200C-0280**

1/2.7" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 2, domet dioda do 30m; fixna optika, vidni ugao 2.8mm- 87.5°,
Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR: DWDR, Max
3.3W (12V DC, IR on), Kuciste: plasticno. Zastita IP67.
Dozna PFA134 , PFA130E



Model: **HAC-HDW1200TQ-0280B**

1/2.7" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 1, domet dioda do 40m; fixna optika, vidni ugao 2.8mm- 87.5°,
Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR: DWDR, Max
3.3W (12V DC, IR on), Kuciste: plasticno.
Dozna PFA130-E



Model: **HAC-HDW1200M-0360/0280**

1/2.7" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 12, domet dioda do 30m; fixna optika, vidni ugao 3.6mm- 87.5°/
2.8mm - 103°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR:
DWDR, Max 3.3W (12V DC, IR on), Kuciste: metalno. Zastita IP67.
Dozna PFA13A , Nosac PFB204W ili PFA152-E.



Model: **HAC-HDW1200M-0280-BLACK**

1/2.7" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 12, domet dioda do 30m; fixna optika, vidni ugao 2.8mm - 103°,
Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR: DWDR, Max
3.3W (12V DC, IR on), Kuciste: metalno. Zastita IP67.
Dozna PFA13A , Nosac PFB204W ili PFA152-E.



Model: **HAC-HFW1200T-0280**

1/2.7" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 1, domet dioda do 30m; fixna optika, vidni ugao 3.6mm- 87.5°/
2.8mm - 103°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR:
DWDR, Max 3.6W (12V DC, IR on), Kuciste: metalno. Zastita IP67.
Dozna PFA134 , Nosac PFA152-E.



Model: HAC-HDW1200TMQ-A-0280

1/2.7" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 2, domet dioda do 60m; fixna optika, vidni ugao/ 2.8mm - 103°,
Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR: DWDR, Max
3.6W (12V DC, IR on),Integrisan mikrofon, Kuciste: metalno. Zastita IP67.
Dozna PFA137 , Nosac PFA130-E.



Model: HAC-HFW1200T-A-0280

1/2.7" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 1, domet dioda do 30m; fixna optika, vidni ugao 3.6mm- 87.5°/
2.8mm - 103°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR:
DWDR, Max 3.6W (12V DC, IR on), Integrisan mikrofon. Kuciste: metalno.
Zastita IP67. Dodaci: Dozna PFA134 , Nosac PFA152-E.



Model: HAC-HFW1200TL-0360

1/2.7" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 2, domet dioda do 40m; fixna optika, vidni ugao 3.6mm- 87.5°/
2.8mm - 103°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR:
DWDR, Max 3.0W (12V DC, IR on), Kuciste: plasticno. Zastita IP67. Dozna
PFA134 , Nosac PFA152-E.



Model: HAC-HDW1200TL-A-0360

1/2.7" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 1, domet dioda do 30m; fixna optika, vidni ugao 3.6mm- 87.5°,
Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR: DWDR, Max
3.0W (12V DC, IR on), Kuciste: metalno. Zastita IP67. Dozna PFA130-E ,
Nosac PFA152-E.



Model: HAC-HDW1200TLMQ-A-0208B

1/2.7" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 1, domet dioda do 30m; fixna optika, vidni ugao 2.8mm- 119°,
Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, Max 3.0W (12V DC,
IR on), Kuciste: metalno.Integrisan mikrofon. Zastita IP67. Dozna PFA130-E
,PFA 13G,Nosac PFA152-E.



Model: HAC-HDW1200TLMQ-A-0208B-BLACK

1/2.7" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 1, domet dioda do 30m; fixna optika, vidni ugao 2.8mm- 119°,
Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, Max 3.0W (12V DC,
IR on), Kuciste: metalno.Integrisan mikrofon. Zastita IP67. Dozna PFA130-E
,PFA13G, Nosac PFA152-E.



Model: **HAC-HFW1200TL-A-0360/0280**

1/2.7" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 2, doimet dioda do 80m; fixna optika, vidni ugao 3.6mm- 87.5°/
2.8mm - 103°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR:
DWDR, Max 4.9W (12V DC, IR on), Kuciste: plasticno. Zastita IP67. Dozna
PFA134 , Nosac PFA152-E.



Model: **HAC-HFW1200TH-I8-0360**

1/2.7" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 2, doimet dioda do 80m; fixna optika, vidni ugao 3.6mm- 87.5°,
Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR: DWDR, Max
4.9W (12V DC, IR on), Kuciste: plasticno. Zastita IP67. Dozna PFA130-E



Model: **HAC-HDBW1200E-0360/0280**

1/2.7" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 12, doimet dioda do 30m; fixna optika, vidni ugao 3.6mm- 87.5°/
2.8mm - 103°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR:
DWDR, Max 3.4W (12V DC, IR on), Kuciste: metalno. Zastita IP67, IK10.
Dozna PFA136 , Nosac PFB203W ili PFA152-E.



Model: **HAC-HDW1231TLMQ-A-0280B starlight**

1/2.7" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 1, doimet dioda do 30m; fixna optika, vidni ugao / 2.8mm - 103°,
Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR: DWDR, Max
3.4W (12V DC, IR on), Integrisan mikorofon. Kuciste: metalno. Zastita
IP67,.Dozna PFA13G , Dozna 130-E.



Model: **HAC-HFW1231TM-I8-A-0360B starlight**

1/2.7" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 2, doimet dioda do 80m; fixna optika, vidni ugao / 3.6mm- 87.5°,
Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR: DWDR, Max
3.4W (12V DC, IR on), Integrisan mikorofon. Kuciste: plastika. Zastita
IP67.Dozna PFA13G , Dozna 130-E.



Model: **HAC-HDW1200EM-A-0360/0280**

1/2.7" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 1, doimet dioda do 50m; fixna optika, vidni ugao 3.6mm- 87.5°/
2.8mm - 103°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR:
DWDR, Max 4.2W (12V DC, IR on), Integrisan mikorofon. Kuciste: metalno.
Zastita IP67.
Dozna PFA130-E ,PFA139, Nosac PFB204W ili PFA152-E.



Model: **HAC-HFW1200D-0360**

1/2.7" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 2, domet dioda do 80m; fixna optika, vidni ugao 3.6mm- 87.5°,
Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR: DWDR, Max
5.4W (12V DC, IR on), Kuciste: metalno. Zastita IP67.
Dozna PFA135, PFA130-E , Nosac PFA152-E.



Model: **HAC-HDW1239T-A-LED-0280B-S2**

1/2.7" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 2, domet dioda do 40m; fixna optika, vidni ugao 3.6mm- 87.5°,
Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR: DWDR, Max
5.4W (12V DC, IR on), Kuciste: plasticno. Zastita IP67.
Dozna PFA139, PFA130-E



Model: **HAC-HFW1239TLM-A-LED**

1/2.7" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 2, domet dioda do 40m; fixna optika, vidni ugao 3.6mm- 87.5°,
Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR: DWDR, Max
5.4W (12V DC, IR on), Kuciste: plasticno. Zastita IP67.
Dozna PFA134, PFA130-E



Model: **HAC-HDW1200T-Z**

1/2.7" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 2, domet dioda do 60m; Motoriz. zoom 2.7-12mm, vidni ugao
105.9°~33.4°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR:
DWDR, Max 5.4W (12V DC, IR on), Kuciste: metalno. Zastita IP67.
Dozna PFA135, PFA130-E , Nosac PFB203W ili PFA152-E.



Model: **HAC-HFW1200R-Z-IRE6**

1/2.7" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 4, domet dioda do 60m; Motoriz. zoom 2.7-12mm, vidni ugao
105.9°~33.4°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR:
DWDR, Max 12.1W (12V DC, IR on), Kuciste: metalno. Zastita IP67.
Dozna PFA130-E , Nosac PFB203W ili PFA152-E.



Model: **HAC-HFW1230TL-A-0360**

1/2.8" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 1, domet dioda do 80m; fixna optika, vidni ugao 3.6mm- 86.9°,
Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR: DWDR, Max
5.3W (12V DC, IR on), Integrisan mikrofon. Kuciste: Plasticno. Zastita IP67.
Dodaci: Dozna PFA134 , Nosac PFA152-E, PFA12A.

Starlight



Starlight

Model: **HAC-HDBW1230E-0360/0280**

1/2.8" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 12, domet dioda do 30m; fixna optika, vidni ugao 3.6mm- 86.9°/
2.8mm - 106°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR:
DWDR, Max 3.1W (12V DC, IR on), Kuciste: metalno. Zastita IP67, IK10.
Dozna PFA136 , Nosac PFB203W ili PFA152-E.



Starlight

Model: **HAC-HDW1230EM-A-0360/0280**

1/2.8" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 1, domet dioda do 50m; fixna optika, vidni ugao 3.6mm- 86.9°/
2.8mm - 106°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR:
DWDR, Max 4.7W (12V DC, IR on), Integrisan mikrofoni. Kuciste: metalno.
Zastita IP67.

Dozna PFA130-E , Nosac PFB204W ili PFA152-E.



Starlight

Model: **HAC-HFW1230D-0360**

1/2.8" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 2, domet dioda do 80m; fixna optika, vidni ugao 3.6mm- 86.9°,
Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR: DWDR, Max
5.6W (12V DC, IR on), Kuciste: metalno. Zastita IP67.
Dozna PFA135, PFA130-E , Nosac PFA152-E.



Starlight

Model: **HAC-HDW1230T-Z-A**

1/2.8" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 2, domet dioda do 60m; Motoriz. zoom 2.7-12mm, vidni ugao
101.7°~32.3°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR:
DWDR, Max 8.2W (12V DC, IR on), Integrisan mikrofoni. Kuciste: metalno.
Zastita IP67.

Dozna PFA135, PFA130-E , Nosac PFB203W ili PFA152-E.



Starlight

Model: **HAC-HFW1230R-Z-IRE6**

1/2.8" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 4, domet dioda do 60m; Motoriz. zoom 2.7-12mm, vidni ugao
101.7°~32.3°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR:
DWDR, Max 12.1W (12V DC, IR on), Kuciste: metalno. Zastita IP67.
Dozna PFA130-E , Nosac PFB203W ili PFA152-E.



Starlight

Model: **HAC-HDW2241TE-0280B**

1/2.8" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 2, domet dioda do 50m; , vidni ugao 121° x 102° x 57°, Frame
Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR: DWDR, Max 12.1W
(12V DC, IR on), Kuciste: plastika. Zastita IP67.
Dozna PFA136 , Nosac PFB203W ili PFA152-E.



Model: **HAC-HFW2241E-A-0360**

1/2.8" CMOS 2mpx cip.2MP 1080P(1920x1080).Broj dioda 2,domet dioda 40m.Fiksna optika 3.6mm-86.9° (110°/52.8°).Frame rate 25/30fps@1080P, 25/30/50/60fps@720P.BLC / HLC / WDR.Kuciste:Aluminijum.Zastita IP67.Dozna PFA 121,PFA152E.

Starlight



Model: **HAC-HDW2241T-A-0360/0280**

1/2.8" CMOS 2mpx cip, 1080P (1920x1080), 2MP broj dioda 2, domet dioda do 50m; Fixna optika, vidni ugao 3.6mm -86.9° / 2.8mm -110°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR: 120dB, Max 5.3W (12V DC, IR on), Integrisan mikrofoni.Kuciste: metalno. Zastita IP67.

Dozna PFA135, PFA130-E , Nosac PFB203W ili PFA152-E.

Starlight



Model: **HAC-HFW2241T-I8-A-0360**

1/2.8" CMOS 2mpx cip, 1080P (1920x1080), 2MP broj dioda 4, domet dioda do 60m; Fixna optika, vidni ugao 3.6mm- 86.9°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR:120dB, Max 10.1W (12V DC, IR on), Integrisan mikrofoni. Kuciste: metalno. Zastita IP67. Dozna PFA130-E , Nosac PFA152-E.

Starlight



Model: **HAC-HFW2241T-Z-A**

1/2.8" CMOS 2mpx cip, 1080P (1920x1080), 2MP broj dioda 4, domet dioda do 80m; Motoriz. zoom 2.7-13.5mm, vidni ugao 108.7°~28.7°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR:120dB, Max 8.2W (12V DC, IR on), Integrisan mikrofoni. Kuciste: metalno. Zastita IP67.

Dozna PFA130-E , Nosac PFA152-E.

Starlight



Model: **HAC-HDW2241T-Z-A**

1/2.8" CMOS 2mpx cip, 1080P (1920x1080), 2MP Smart infracrvene diode, domet dioda do 60m; Motoriz. zoom 2.7-13.5mm, vidni ugao 108.7°~28.7°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR:120dB, Max 8.2W (12V DC, IR on), Integrisan mikrofoni. Kuciste: metalno. Zastita IP67.

Dozna PFA130-E , Nosac PFA152-E.

Starlight



Model: **HAC-HDBW2241R-Z**

1/2.8" CMOS 2mpx cip.2MP 1080P (1920x1080).Domet dioda do 30m.Motorizovani zoom 2.7-13.5mm,vidni ugao 108.7°~28.7°.Frame rate 25/30fps@1080P, 25/30/50/60fps@720P .Npajanje 12V DC ±30%.Kuciste :Aluminijum.Zastita IP67, IK10.Dozna PFA 137.

Starlight

SMP HDCVI KAMERE



Model: **HAC-HDW1500TRQ-0280B-S2**
1/2.7" CMOS 5mpx cip, 5MP(2592×1944),
broj dioda 2, domet dioda do 25m; fixna optika, vidni ugao 2.8mm - 98°,
Frame Rate: 20fps@5MP, 25/30fps@4MP, 25/30fps@1080P, WDR: DWDR,
Max 4.2W (12V DC, IR on). Kuciste: plasticno. Zastita IP50. Nosac PFB205W



Model: **HAC-HFW1500C-0280B-S2**
1/2.7" CMOS 5mpx cip, 5MP(2592×1944),
broj dioda 3, domet dioda do 30m; fixna optika, vidni ugao 2.8mm - 98°,
Frame Rate: 20fps@5MP, 25/30fps@4MP, 25/30fps@1080P, WDR: DWDR,
Max 4.2W (12V DC, IR on). Kuciste: plasticno. Zastita IP65. Nosac
PFA134, PFA130-E.



Model: **HAC-HDW1500TLMQ-A-0280B-S2**
1/2.7" CMOS 5mpx cip, 5MP(2592×1944),
broj dioda 1, domet dioda do 30m; fixna optika, vidni ugao 2.8mm - 98°,
Frame Rate: 20fps@5MP, 25/30fps@4MP, 25/30fps@1080P, WDR: DWDR,
Max 4.2W (12V DC, IR on), Integrisan mikrofon. Kuciste: metalno. Zastita
IP67. Dozna PFA13G , Nosac PFB205W



Model: **HAC-HFW1500TH-I8-0360B**
1/2.7" CMOS 5mpx cip, 5MP(2592×1944),
broj dioda 2, domet dioda do 80m; fixna optika, vidni ugao 3.6mm- 77.5°,
Frame Rate: 20fps@5MP, 25/30fps@4MP, 25/30fps@1080P, WDR: DWDR,
Max 4.2W (12V DC, IR on). Kuciste: plastika. Zastita IP67. Dozna PFA135 ,
Nosac PFA152-E



Model: **HAC-HDW1500TMQ-A-0280B**
1/2.7" CMOS 5mpx cip, 5MP(2592×1944),
broj dioda 2, domet dioda do 60m; fixna optika, vidni ugao 2.8mm - 98°,
Frame Rate: 20fps@5MP, 25/30fps@4MP, 25/30fps@1080P, WDR: DWDR,
Max 4.2W (12V DC, IR on), Integrisan mikrofon. Kuciste: metalno. Zastita
IP67. Nosac PFB205W.



Model: **HAC-HFW1500T-A-0360/0280**
1/2.7" CMOS 5mpx cip, 5MP(2592×1944),
broj dioda 1, domet dioda do 30m; fixna optika, vidni ugao 3.6mm- 77.5°/
2.8mm - 93°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR:
DWDR, Max 3.7W (12V DC, IR on), Integrisan mikrofon. Kuciste: metalno.
Zastita IP67. Dodaci: Dozna PFA134 , Nosac PFA152-E.



Model: **HAC-HFW1500TL-A-0360/0280**

1/2.7" CMOS 5mpx cip, 5MP(2592×1944),
broj dioda 2, domet dioda do 80m; fixna optika, vidni ugao 3.6mm- 77.5° /
2.8mm - 98°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR:
DWDR, Max 4.9W (12V DC, IR on), Integrisan mikrofon. Kuciste: plasticno.
Zastita IP67. Dozna PFA134 , Nosac PFA152-E.



Model: **HAC-HFW1500D-0360**

1/3" CMOS 5mpx cip, 5MP(2592×1944),
broj dioda 2, domet dioda do 80m; fixna optika, vidni ugao 3.6mm- 77.5° ,
Frame Rate:20fps@5MP, 25/30fps@4MP, 25/30fps@1080P, WDR: DWDR,
Max 4.6W (12V DC, IR on),
Kuciste: metalno. Zastita IP67.
Dozna PFA135, PFA130-E , Nosac PFA152-E.



Model: **HAC-HDW1500T-Z-A-2712**

1/2.7" CMOS 5mpx cip, 5MP(2592×1944),
broj dioda 2, domet dioda do 60m; Motoriz. zoom 2.7-12mm, vidni ugao
98°~34°, Frame Rate: 20fps@5MP, 25/30fps@4MP, 25/30fps@1080P,
WDR: DWDR, Max 8.2W (12V DC, IR on), Integrisan mikrofon.Kuciste:
metalno. Zastita IP67.
Dozna PFA130-E , Nosac PFB203W ili PFA152-E.



Model: **HAC-HFW1500R-Z-IRE6-A-2712**

1/2.7" CMOS 5mpx cip, 5MP(2592×1944),
broj dioda 4, domet dioda do 60m; Motoriz. zoom 2.7-12mm, vidni ugao
98°~34°, Frame Rate: 20fps@5MP, 25/30fps@4MP, 25/30fps@1080P,
WDR: DWDR, Max 12W (12V DC, IR on), Integrisan mikrofon.Kuciste:
metalno. Zastita IP67.
Dozna PFA130-E , Nosac PFA152-E.



Model:**HAC-HDW1509T-A-LED-0360B**

1/2.7 inch CMOS 5mpx cip,5MP(2592x1944),
broj dioda 1,domet LED dioda do 20m;fixna optika
3.6mm,vidni ugao 111°~83,frame rate:20fps@5MP,
25fps@4MP,25fps@1080P,WDR: DWDR,Max 3.0W (12V DC, white light
on),Integrisan mikrofon.Kuciste:Metalno duz untrasnjosti kucista.Zastita
IP67,Dodaci:dozna 130-E



Model:**HAC-ME1509TH-PV-0360B TIOC**

1/2.7 inch CMOS 5mpx cip,5MP(2592x1944),
broj dioda 2,plavo-crveno svetlo,domet LED dioda do 40m;fixna optika
3.6mm,vidni ugao 111°~83,frame rate:20fps@5MP,
25fps@4MP,25fps@1080P,WDR: DWDR,Max 3.0W (12V DC, white light
on).Kuciste:Metalno kuciste.Zastita IP67,Dodaci:dozna 130-E.



Model:HAC-HDW1509TL-A-LED-0360B

1/2.7 inch CMOS 5mpx cip,5MP(2592x1944), broj dioda 1,domet LED dioda do 20m;fixna optika 3.6mm,vidni ugao 111°~83,frame rate:20fps@5MP, 25fps@4MP,25fps@1080P,WDR: DWDR,Max 3.0W (12V DC, white light on),Integrisan mikrofon.Kuciste:plasticno. Zastita IP67,Dodaci:dozna 130-E



Model:HAC-HFW1509T-A-LED-0360B

1/2.7 inch CMOS 5mpx cip,5MP(2592x1944), broj dioda 1 ,domet LED dioda do 20m;fixna optika 3.6mm,vidni ugao 111°~83,frame rate:20fps@5MP, 25fps@4MP,25fps@1080P,WDR: DWDR,Max 3.0W (12V DC, white light on),Integrisan mikrofon.Kuciste:Metalno. Zastita IP67,Dodaci:dozna 134



Model: HAC-HFW1509TLM-A-LED-0360B

1/2.7" CMOS 5mpx cip, 5MP(2592x1944), broj dioda 2, domet LED dioda do 40m;fixna optika 3.6mm,vidni ugao 111°~83, Frame rate:20fps@5MP, 25fps@4MP,25fps@1080P, WDR: DWDR,Max 5.0W (12V DC, white light on), Integrisan mikrofon.Kuciste:plasticno. Zastita IP67,Dodaci:dozna 134,Nosac 152-E



Starlight

Model: HAC-HDW2501TMQ-A

1/2.8" CMOS 5mpx cip, 5MP(2592x1944), broj dioda 2, domet dioda do 60m; Fixna optika, vidni ugao 98°~49°, Frame Rate: 20fps@5MP, 25/30fps@4MP, 25/30fps@1080P, WDR: DWDR, Max 10W (12V DC, IR on), Integrisan mikrofon.Kuciste: aluminijum. Zastita IP67. Dozna PFA130-E,PFA137



Starlight

Model: HAC-HFW2501TU-A-0360B

1/2.8" CMOS 5mpx cip, 5MP(2592x1944), broj dioda 4, domet dioda do 80m; Fixna optika, vidni ugao 98°~49°, Frame Rate: 20fps@5MP, 25/30fps@4MP, 25/30fps@1080P, WDR: DWDR, Max 10W (12V DC, IR on), Integrisan mikrofon.Kuciste: metalno iznutra. Zastita IP67. Dozna PFA130-E,PFA135



Starlight

Model: HAC-HDW2501T-A

1/2.8" CMOS 5mpx cip, 5MP(2592x1944), broj dioda 2, domet dioda do 56m; Fixna optika, vidni ugao 98°~49°, Frame Rate: 20fps@5MP, 25/30fps@4MP, 25/30fps@1080P, WDR: DWDR, Max 10W (12V DC, IR on), Integrisan mikrofon.Kuciste: aluminijum. Zastita IP67. Dozna PFA130-E



Model: **HAC-HFW2501T-I8-A**

1/2.8" CMOS 5mpx cip, 5MP(2592×1944), broj dioda 4, domet dioda do 80m; Fixna optika, vidni ugao 102°~29°, Frame Rate: 20fps@5MP, 25/30fps@4MP, 25/30fps@1080P, WDR: DWDR, Max 12.4W (12V DC, IR on), Integrisan mikrofon.Kuciste: aluminijum. Zastita IP67. Dozna PFA130-E , Nosac PFA152-E,

Starlight



Model: **HAC-HDW2501T-Z-A**

1/2.8" CMOS 5mpx cip, 5MP(2592×1944), broj dioda 2, domet dioda do 60m; Motoriz. zoom 2.7-13.5mm, vidni ugao 102°~29°, Frame Rate: 20fps@5MP, 25/30fps@4MP, 25/30fps@1080P, WDR: DWDR, Max 10W (12V DC, IR on), Integrisan mikrofon.Kuciste: metalno. Zastita IP67.

Starlight

Dozna PFA130-E , Nosac PFB203W ili PFA152-E.



Model: **HAC-HFW2501TP-Z-A**

1/2.8" CMOS 5mpx cip, 5MP(2592×1944), broj dioda 4, domet dioda do 80m; Motoriz. zoom 2.7-13.5mm, vidni ugao 102°~29°, Frame Rate: 20fps@5MP, 25/30fps@4MP, 25/30fps@1080P, WDR: DWDR, Max 12.4W (12V DC, IR on), Integrisan mikrofon.Kuciste: metalno. Zastita IP67.

Starlight

Dozna PFA130-E , Nosac PFA152-E, PFA151.

8MP HDCVI KAMERE



Model: **HAC-HDW1801TL-A-028**

1/2.7 inch CMOS 8mpx cip. 8MP 3840 (H)×2160 (V), 4K.broj dioda 1,domet dioda 30m.Fiksna optika.2.8mm: 125°×105°×56° (diagonal×horizontal×vertical).CVI: 4K@15fps; 5M@20fps; 4M@25fps/30fps AHD: 4K@15fps; 5M@20fps; 4M@25fps/30fps Integrisan mikrofon.Kuciste unutrašnjost metal spolja plastika.IP67, 12V±30%DC.Do zna PFA12A



Model: **HAC-HDW1801M-028**

1/2.7 inch CMOS 8mpx cip. 8MP 3840 (H)×2160 (V), 4K.broj dioda 1,domet dioda 30m.Fiksna optika.2.8mm: 125°×105°×56° (diagonal×horizontal×vertical).CVI: 4K@15fps; 5M@20fps; 4M@25fps/30fps AHD: 4K@15fps; 5M@20fps; 4M@25fps/30fps.Kuciste unutrašnjost metal.IP67, 12V±30%DC.Do zna PFA13A-E,PFB204W



Model: **HAC-HDW2802T-A-028**

1/1.8" CMOS 8mpx cip. 8MP 3840 (H)×2160 (V), 4K.broj dioda 2,domet dioda 50m.Fiksna optika.2.8mm: 125°×105°×56° (diagonal×horizontal×vertical).CVI: 4K@15fps; 5M@20fps; 4M@25fps/30fps AHD: 4K@15fps; 5M@20fps; 4M@25fps/30fps.Kuciste:Aluminijum.IP67, 12V±30%DC.Dozna PFA130E

Starlight



Model: **HAC-HDBW2802R-028**

1/1.8" CMOS 8mpx cip. 8MP 3840 (H)×2160 (V), 4K.broj dioda 1,domet dioda 30m.Fiksna optika.2.8mm: 125°×105°×56° (diagonal×horizontal×vertical).CVI: 4K@15fps; 5M@20fps; 4M@25fps/30fps AHD: 4K@15fps; 5M@20fps; 4M@25fps/30fps.Kuciste:Aluminijum.IP67, IK10,12V±30%DC.Dozna PFA137,PFB203W

Starlight

PTZ KAMERE



Starlight

Model: **SD22204-GC-LB**

1/2.8" STARVIS CMOS 2mpx cip, 1080P(1920×1080), 4X opticki zoom, optika:2.7 mm–11 mm ; vidni ugao H: 112.5°–30°; V: 54.2°–19.9°; D: 122.3°–40.6°, Frame Rate:25/30fps@1080P, 25/30/50/60fps@720P, BLC / HLC / WDR(120dB), Napajanje: AC24V/1.5A(±10%); Potrosnja: 5W, Kuciste: metalno. Zastita IP66, IK10.

Nosac PFB203W,PFB305W,PFA152-E



Starlight

Model: **SD42212I-HC**

1/2.8" STARVIS CMOS 2mpx cip, 1080P(1920×1080), 12X opticki zoom, optika: 5.3mm~64mm; vidni ugao 58.2° ~ 4.8°, Frame Rate:25/30fps@1080P, 25/30/50/60fps@720P,OSD meni, BLC / HLC / WDR(120dB), Napajanje: AC24V/1.5A(±10%); Potrosnja: 10W, Kuciste: metalno. Zastita IP66, IK10.

Nosac PFA102, PFB300C, PFA150, PFA151.



Starlight

Model: **SD40212I-HC**

1/2.8" STARVIS CMOS 2mpx cip, 1080P(1920×1080), 12X opticki zoom, optika: 5.3mm~64mm; vidni ugao 58.2° ~ 4.8°, Frame Rate:25/30fps@1080P, 25/30/50/60fps@720P,OSD meni,BLC / HLC / WDR(120dB), Napajanje: AC24V/1.5A(±10%); Potrosnja: 10W, Kuciste: metalno. Zastita IP66, IK10.

Nosac PFB300C, PFA150, PFA151, PFA152-E.



Starlight

Model: **SD42215-HC-LA**

1/2.8" STARVIS CMOS 2mpx cip, 1080P(1920×1080), 15X opticki zoom, optika: 5.3mm~64mm; vidni ugao 58.2° ~ 4.8°, Frame Rate:25/30fps@1080P, 25/30/50/60fps@720P,OSD meni,BLC / HLC / WDR(120dB), Napajanje: AC24V/1.5A(±10%); Potrosnja: 10W, Kuciste: metalno. Zastita IP66, IK10.

Nosac PFB300C, PFA150, PFA151,



Starlight

Model: **SD49225-HC-LA**

1/2.8" STARVIS CMOS 2mpx cip, 1080P(1920×1080), 25X opticki zoom,domet do 100m. optika: 4.8mm~120mm; vidni ugao 67.5° ~ 3.2°, Frame Rate:Sub stream1: D1/CIF(1 ~ 25/30fps),Sub stream2: 720P/D1/CIF(1 ~ 25/30fps)AC24V/1.5A(±10%); Potrosnja: DC 12V/3A, Kuciste: metalno. Zastita IP66,



Starlight

Model: **SD49225T-HN**

1/2.8" STARVIS CMOS 2mpx cip, 1080P(1920×1080), 25X opticki zoom, do met do 100m. optika: 4.8mm~120mm; vidni ugao 62.8° ~ 2.6°, Frame Rate:Sub stream1: D1/CIF(1 ~ 25/30fps),Sub stream2: 720P/D1/CIF(1 ~ 25/30fps)AC24V/1.5A(±10%); Potrosnja: DC 12V/3A, PoE+(802.3at), Kuciste: metalno. Zastita IP66, IK10.



Starlight

Model: **SD50225I-HC**

1/2.8" STARVIS CMOS 2mpx cip, 1080P(1920×1080), 25X opticki zoom, optika: 4.8mm~120mm; vidni ugao 62.8° ~ 2.6°, Frame Rate:25/30fps@1080P, 25/30/50/60fps@720P,OSD meni,BLC / HLC / WDR(120dB), Napajanje: AC24V/1.5A(±10%); Potrosnja: 13W23W(Heater on), Kuciste: metalno. Zastita IP66, IK10.
Nosac PFB300C, PFA150, PFA151.



Starlight

Model: **SD59225I-HC**

1/2.8" STARVIS CMOS 2mpx cip, 1080P(1920×1080), 25X opticki zoom, broj dioda 4, do met dioda do 150m; optika: 4.8mm~120mm; vidni ugao 62.8° ~ 2.6°, Frame Rate:25/30fps@1080P, 25/30/50/60fps@720P,OSD meni,BLC / HLC / WDR(120dB), Napajanje: AC24V/3A(±10%); Potrosnja: 13W,23W (IR on), Kuciste: metalno. Zastita IP66, IK10.
Nosac PFB300C, PFA150, PFA151.



Starlight

Model: **SD50230I-HC**

1/2.8" STARVIS CMOS 2mpx cip, 1080P(1920×1080), 30X opticki zoom, optika: 4.5mm~135mm vidni ugao 67.8° ~ 2.4°, Frame Rate:25/30fps@1080P, 25/30/50/60fps@720P,OSD meni,BLC / HLC / WDR(120dB), Napajanje: AC24V/1.5A(±10%); Potrosnja: 13W23W(Heater on), Kuciste: metalno. Zastita IP66, IK10.
Nosac PFB300C, PFA150, PFA151.



Starlight

Model: **SD50232-HC-LA**

1/2.8" STARVIS CMOS 2mpx cip, 1080P(1920×1080), 32X opticki zoom, optika: 4.5mm~135mm vidni ugao 67.8° ~ 2.4°, Frame Rate:25/30fps@1080P, 25/30/50/60fps@720P,OSD meni,BLC / HLC / WDR(120dB), Napajanje: AC24V/1.5A(±10%); Potrosnja: 13W23W(Heater on), Kuciste: metalno. Zastita IP66, IK10.
Nosac PFB300C, PFA150, PFA151.

SNIMACI



Model: XVR1B04

4-kanalni H.265+/H.265 dvotočna video kompresija
Podržava HDCVI/AHD/TVI/CVBS/IP video ulaze
Maksimalno 5 kanala za IP kamere, svaki kanal do 2MP/6MP; Maksimalna propusna širina 20/40Mbps
Velika udaljenost prenosa preko koaksijalnog kabla
Podržava 1 SATA HDD, do 6TB



Model: XVR1B04-I

4-kanalni Penta-bridž 1080N/720p Cooper 1U 1HDD VizSense digitalni video rekorder.H.265+/H.265 dvotočna video kompresija.Podržava punokanalno AI-kodiranje.Podržava HDCVI/AHD/TVI/CVBS/IP video ulaze.Maksimalno 5 kanala za IP kameru, svaki kanal do 2MP; Maksimalna propusna moć do 20 Mbps.Do 4 kanala video strim (analogni kanal) SMD Plus



Model: XVR1B08

8-kanalni Penta-bridž 1080N/720P Cooper 1U digitalni video rekorder.H.265+/H.265 dvotočna video kompresija
Podržava HDCVI/AHD/TVI/CVBS/IP video ulaze
Maksimalno 10 kanala za kamere, svaki kanal do 2MP/6MP; Maksimalna propusna širina 20/40Mbps
Velika udaljenost prenosa preko koaksijalnog kabla
Podržava 1 SATA HDD, do 6TB



Model: XVR1B08-I

8-kanalni Penta-bridž 1080N/720P Cooper 1U digitalni video rekorder.H.265+/H.265 dvotočna video kompresija
Podržava HDCVI/AHD/TVI/CVBS/IP video ulaze
Maksimalno 10 kanala za kamere, svaki kanal do 2MP/6MP; Maksimalna propusna širina 20/40Mbps
Velika udaljenost prenosa preko koaksijalnog kabla
Podržava 1 SATA HDD, do 6TB. Full channel AI-Coding



Model: XVR1B16-I

16-kanalni Penta-bridž 1080N/720p kompaktni 1U 1HDD VizSense digitalni video rekorder.H.265+/H.265 dvotočna video kompresija.Podržava punokanalno AI-kodiranje.Podržava HDCVI/AHD/TVI/CVBS/IP video ulaze
Maksimalno 18 kanala za ulaz IP kamere, svaki kanal do 6MP; Maksimalna propusna moć do 64 Mbps.Velika udaljenost prenosa preko koaksijalnog kabla.Do 8 kanala video strim (analogni kanal) SMD Plus



Model: XVR5104HS-I2

4ch snimac (HDCVI, HDTVI, AHD, CVBS, IP); dodatno 4+2 IP kamere do 6mpx; Kompresija: H.265+/H.265/H.264+/H.264; Rezolucija snimanja :5M-N(1~10fps), 4M-N/1080P(1~15fps), 1080N/720P/960H/D1/CIF (1~25/30fps); 1 HDMI ,1 VGA; Rezolucija prikaza: 1920×1080, 1280×1024, 1280×720; 1 audio ulaz, 1 audio izlaz; audio preko koaksijalnog kabla; 1HDD do 6TB; Napajanje 12V/1.5A



Model: XVR5108HS-I2

8ch snimac (HDCVI, HDTVI, AHD, CVBS, IP); dodatno 8+4 IP kamere do 6mpx; Kompresija: H.265+/H.265/H.264+/H.264; Rezolucija snimanja :5M-N(1~10fps), 4M-N/1080P(1~15fps), 1080N/720P/960H/D1/CIF (1~25/30fps); 1 HDMI ,1 VGA; Rezolucija prikaza: 1920×1080, 1280×1024, 1280×720; 1 audio ulaz, 1 audio izlaz; audio preko koaksijalnog kabla; 1HDD do 6TB; Napajanje 12V/1.5A



Model: XVR5116HS-I2

16ch snimac (HDCVI, HDTVI, AHD, CVBS, IP); dodatno 16+ 8 IP mere do 6mpx; Kompresija: H.265+/H.265/H.264+/H.264; Rezolucija snimanja :5M-N(1~10fps), 4M-N/1080P(1~15fps), 1080N/720P/960H/D1/CIF (1~25/30fps); 1 HDMI ,1 VGA; Rezolucija prikaza: 1920×1080, 1280×1024, 1280×720; 1 audio ulaz, 1 audio izlaz; audio preko koaksijalnog kabla; 1HDD do 6TB; Napajanje 12V/1.5A



Model: XVR5104HS-4KL-I2

4ch snimac (HDCVI/AHD/TVI/CVBS/IP); dodatno 4+4 IP kamere do 8mpx; Kompresija: H.265+/H.265/H.264+/H.264; Rezolucija snimanja : 4K/6MP/5MP/4K-N/4MP/3MP/4M-N, 1080P/720P/960H/D1/CIF; 1 HDMI ,1 VGA; Rezolucija prikaza: HDMI: 3840×2160, 1920×1080, 1280×1024, 1280×720
VGA: 1920×1080, 1280×1024, 1280×720 ; 1 audio ulaz, 1 audio izlaz; audio preko koaksijalnog kabla; 1HDD do 10TB; Napajanje 12V/2A



Model: XVR5108HS-4KL-I3

8ch snimac (HDCVI/AHD/TVI/CVBS/IP); dodatno 8+8 IP kamere do 8mpx; Kompresija: H.265+/H.265/H.264+/H.264; Rezolucija snimanja : 4K/6MP/5MP/4K-N/4MP/3MP/4M-N, 1080P/720P/960H/D1/CIF; 1 HDMI ,1 VGA; Rezolucija prikaza: HDMI: 3840×2160, 1920×1080, 1280×1024, 1280×720
VGA: 1920×1080, 1280×1024, 1280×720 ; 1 audio ulaz, 1 audio izlaz; audio preko koaksijalnog kabla; 1HDD do 10TB; Napajanje 12V/2A



Model: XVR5216AN-I2

16ch snimac (HDCVI, HDTVI, AHD, CVBS, IP); dodatno 16+8 IP kamere do 6mpx; Kompresija: H.265+/H.265/H.264+/H.264; Rezolucija snimanja: 5M-N(1~10fps), 4M-N/1080P(1~15fps), 1080N/720P/960H/D1/CIF (1~25/30fps); 1 HDMI ,1 VGA; Rezolucija prikaza: HDMI:3840×2160, 2560×1440, VGA: 1920×1080, 1280×1024, 1280×720 1audio ulaz, 1 audio izlaz; audio preko koaksijalnog kabla; 2HDD do 10TB; Napajanje 12V/1.5A



Wiz Sense

Model: XVR5216A-4KL-I2

16ch snimac (HDCVI, HDTVI, AHD, CVBS, IP).odatno 16+16 IP kamere do 8mpx;Kompresija:H.265+/H.265/H.264+/H.264; Rezolucija snimanja:4MN/1080P/720P/960H/D1/CIF(1fps–25/30fps); Substream:960H(1fps–15fps);D1/CIF(1fps–25/30fps).1 HDMI ,1 VGA;Rezolucija prikaza: HDMI:3840×2160, 2560×1440, VGA: 1920×1080, 1280×1024, 1280×720.720 1 audio ulaz, 1 audio izlaz; audio preko koaksijalnog kabla; 2HDD do 10TB; Napajanje:DC 12V/5A



Wiz Sense

Model: XVR5116HE-4KL-I2

16ch snimac (HDCVI, HDTVI, AHD, CVBS, IP); Max 32 kanala za IP kamere do 8mpx; Kompresija: H.265+/H.265/H.264+/H.264; Rezolucijasnimanja:4K(1fps–7fps);6MP(1fps–10fps);5MP(1fps–12fps); 4K-N, 4MP/3MP(1fps–15fps); 4M-N/1080P/720P/960H/D1/CIF (1fps–25/30fps);Sub stream:960H(1fps–15fps);D1/CIF(1fps–25/30fps) Rezolucija prikaza: HDMI:3840×2160, 2560×1440, 1920×1080, 1280×1024, 1280×720,VGA: 1920×1080, 1280×1024, 1280×720; 1audio ulaz, 1 audio izlaz; audio preko koaksijalnog kabla; 1HDD do 10TB; Napajanje 12V/2A



Wiz Sense

Model: XVR5232AN-I2

32ch snimac (HDCVI, HDTVI, AHD, CVBS, IP); Max 32 kanala za IP kamere do 6mpx; Kompresija: H.265+/H.265/H.264+/H.264; Rezolucijasnimanja:5M-N, 4M-N, 1080P, 1080N, 720P, 960H, D1, CIF;Sub stream:960H(1fps–15fps);D1/CIF(1fps–25/30fps) Rezolucija prikaza: HDMI:3840×2160, 2560×1440, 1920×1080, 1280×1024, 1280×720,VGA: 1920×1080, 1280×1024, 1280×720; 1audio ulaz, 1 audio izlaz; audio preko koaksijalnog kabla; 2HDD do 10TB; Napajanje 12V/5A

Model: XVR7216A-4KL-X

16ch snimac (HDCVI, HDTVI, AHD, CVBS, IP); Max 32 kanala za IP kamere do 8mpx;H.265+/H.265 dual-stream video compression.4K, 6MP, 5MP, 4MP, 1080P@25/30fps, 720P@50/60fps, 720P@25/30fps.4K(1~7fps); 6MP(1~10fps); 5MP(1~12fps); 4MP/3MP(1~15fps); 4M-N/1080P/720P/960H/D1/CIF/QCIF (1~25/30fps).1 HDMI, 1 VGA



IP VIDEO NADZOR 2MP



Model: IPC-A22EP-A

Kamera za unutrašnju upotrebu. 1080P Full HD. Pokretna kamera od 360°. WiFi povezivanje na tel. Memoriska kartica do 128GB (ne dolazi u kompletu). Detekcija pokreta ljudi, bebin plac, razbijanje stakla i drugih neubicajnih zvukova. Rezim privatnosti. Zvucnik i Mikrofon. Alexa Google Assistant. Nocni mod



Model: IPC-HDW1230T1-0280B-S4

1/2.8" CMOS 2mpx cip, 1080P (1920x1080), 2MP
broj dioda 1, domet dioda do 30m; fixna optika, vidni ugao 2.8mm - 106°,
Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR: 120dB, 12V
DC/PoE, Max 6.5W (12V DC, IR on) Kuciste: metalno+plastika. Zastita IP67.
IVS Analitika: Intrusion; tripwire.
Dozna PFA136, Nosac PFA152-E.



Model: IPC-HFW1230S1-028B-S5

1/2.8" CMOS 2mpx cip, 1080P (1920x1080), 2MP
broj dioda 1, domet dioda do 30m; fixna optika, vidni ugao 2.8mm - 106°,
Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR: 120dB, 12V
DC/PoE, Max 4.9W (12V DC, IR on) Kuciste: metal+plastika. Zastita IP67. IVS
Analitika: Intrusion; tripwire.
Dozna PFA134, Nosac PFA152-E.



Model: IPC-HDW1239T1-LED-028B-S5

1/2.7" CMOS 2mpx cip, 1080P (1920x1080), 2MP
broj dioda 1, domet dioda do 10m; fixna optika, vidni ugao 2.8mm - 106°,
Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR: 120dB, 12V
DC/PoE, Max 4.9W (12V DC, IR on) Kuciste: metal+plastika. Zastita IP67.
Dozna PFA136, Nosac PFA152-E.



Full-color



Model: IPC-HFW1239S1-LED-028B-S5

1/2.7" CMOS 2mpx cip, 1080P (1920x1080), 2MP
broj dioda 1, domet dioda do 10m; fixna optika, vidni ugao 2.8mm - 106°,
Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR: 120dB, 12V
DC/PoE, Max 4.9W (12V DC, IR on) Kuciste: metal+plastika. Zastita IP67.
Dozna PFA134, Nosac PFA152-E.



Full-color



Model: IPC-HDW2231T-AS-0360/0280

1/2.8" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 2, domet dioda do 30m; fixna optika, vidni ugao 3.6mm- 87°/
2.8mm - 106°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR:
120dB, 12V DC/PoE ,Max 6.5W (12V DC, IR on), Micro SD Card (support max.
256 GB)

Kuciste: metalno. Zastita IP67. IVS Analitika: Intrusion; tripwire.
Dozna PFA130-E , Nosac PFA152-E.



Model: IPC-HDBW2231E-S-0280

1/2.8" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 3, domet dioda do 30m; fixna optika, vidni ugao 2.8mm - 106°,
Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR: 120dB, 12V
DC/PoE ,Max 6.5W (12V DC, IR on), Micro SD Card (support max. 256 GB)

Kuciste: metalno. Zastita IP67. IVS Analitika: Intrusion; tripwire.
Dozna PFA130-E , Nosac PFA152-E.



Model: IPC-HFW2231S-S-0360B/0280

1/2.8" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 1, domet dioda do 30m; fixna optika, vidni ugao 3.6mm- 87°/
2.8mm - 106°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR:
120dB, 12V DC/PoE ,Max 4.9W (12V DC, IR on), Micro SD Card (support max.
256 GB)

Kuciste: metalno. Zastita IP67. IVS Analitika: Intrusion; tripwire.
Dozna PFA134 , Nosac PFA152-E.



Model: IPC-HDBW1230E-S-0360B-S1

1/2.7" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 24, domet dioda do 30m; fixna optika, vidni ugao 3.6mm- 92°/
2.8mm - 104°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR:
120dB, 12V DC/PoE ,Max 5.5W (12V DC, IR on), Micro SD Card (support max.
256 GB)

Kuciste: metalno. Zastita IP67, IK10. IVS Analitika: Intrusion; tripwire.
Dozna PFA136, Nosac PFA152-E.



Model: IPC-HFW1230T-ZS-S5

1/2.7" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 2, domet dioda do 50m; motorizovani zoom, Frame Rate:
25/30fps@1080P, 25/30/50/60fps@720P, WDR: 120dB, 12V DC/PoE ,Max
5.5W (12V DC, IR on), Micro SD Card (support max. 256 GB)

Kuciste: metalno. Zastita IP67, IK10. IVS Analitika: Intrusion; tripwire.



Model: IPC-HDBW1235E-W-028

1/2.7" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 18, domet dioda do 30m; fixna optika, vidni ugao 2.8mm - 104°,
Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR: 120dB, 12V
DC/PoE ,Max 5.5W (12V DC, IR on), Micro SD Card (support max. 256 GB)
Kuciste: metalno. Zastita IP67, IK10.Dozna PFA136,PFA152-E



Model: IPC-HFW1235S-W-028

1/2.7" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 18, domet dioda do 30m; fixna optika, vidni ugao 2.8mm - 104°,
Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR: 120dB, 12V
DC/PoE ,Max 5.5W (12V DC, IR on), Micro SD Card (support max. 256 GB)
Kuciste: metalno. Zastita IP67, IK10.Dozna PFA134,PFA152-E



Model: IPC-HDW1230T-ZS-2812-S5

1/2.7" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 2, domet dioda do 40m; Motoriz.zoom, vidni ugao 2.7-13.5mm,
Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR: 120dB, 12V
DC/PoE ,Max 5.5W (12V DC, IR on), Micro SD Card (support max. 256 GB)
Kuciste: metalno. Zastita IP67.Dozna PFB205W,PFA152-E



Model: IPC-HDBW2231R-ZS-S2

1/2.8" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 2, domet dioda do 40m; Motoriz. zoom 2.7-13.5mm, vidni ugao
109°-28°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR:
120dB, 12V DC/PoE ,Max 6.4W (12V DC, IR on), Micro SD Card (support max.
256 GB)
Kuciste: metalno. Zastita IP67, IK10. IVS Analitika: Intrusion; tripwire.
Dozna PFA136, PFA152-E.



Model: IPC-HFW2231T-ZS-S2

1/2.8" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 4, domet dioda do 60m; Motoriz. zoom 2.7-13.5mm, vidni ugao
109°-28°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P,
WDR:120dB, 12V DC/PoE , Max 9.6W (12V DC, IR on), Micro SD Card
(support max. 256 GB) Integrisan mikrofona. Kuciste: metalno. Zastita
IP67,IK10. Dozna PFA130-E , Nosac PFA152-E.



Model: IPC-HDW3249H-AS-PV-0280B Tioc

1/2.8" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 1, domet dioda do 30m;fiksna optika , vidni ugao 107°-28°,
Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR:120dB, 12V
DC/PoE , Max 9.6W (12V DC, IR on), Micro SD Card (support max. 256 GB)
Integrisan mikrofon. Kuciste: metalno. Zastita IP67. Dozna PFA137



Model: IPC-HFW3249T1-AS-PV-0280B Tioc

1/2.8" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 2, domet dioda do 40m;fiksna optika, vidni ugao 109°-28°, Frame
Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR:120dB, 12V DC/PoE ,
Max 9.6W (12V DC, IR on), Micro SD Card (support max. 256 GB) Integrisan
mikrofon. Kuciste: metalno. Zastita IP67, Dozna PFA130-E , Nosac PFA152-E.



Model: IPC-HDBW3241F-AS-M

1/2.8" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 8, domet dioda do 30m;fiksna optika, vidni ugao 109°-28°, Frame
Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR:120dB, 12V DC/PoE ,
Max 9.6W (12V DC, IR on), Micro SD Card (support max. 256 GB) Integrisan
mikrofon. Kuciste: metalno. Zastita IP67,IK10, Dozna PFA139 , Nosac
PFA152-E.



Model: IPC-HDBW3241E-AS-0280B

1/2.8" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 5, domet dioda do 50m;fiksna optika, vidni ugao 106°, Frame
Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR:120dB, 12V DC/PoE ,
Max 9.6W (12V DC, IR on), Micro SD Card (support max. 256 GB) Integrisan
mikrofon. Kuciste: metalno. Zastita IP67,IK10, Dozna PFA136 , Nosac
PFA152-E.



Model: IPC-HDBW4231F-AS-0360/0280

1/2.8" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 10, domet dioda do 20m; fixna optika, vidni ugao 3.6mm- 87°/
2.8mm - 104°, Integrisan mikrofon, Frame Rate:Main Stream: 1080P
(1~50/60fps), Sub Stream: D1(1~50/60fps), Third Stream:
1080P(1~25/30fps), WDR: 120dB, 12V DC/PoE ,Max 4.5W (12V DC, IR on),
Micro SD Card (support max. 256 GB)
Kuciste: metalno. Zastita IP67, IK10. IVS Analitika: Intrusion; tripwire,
detekcija lica.
Dozna PFA139.



FullColour

Model: IPC-HDW2239T-AS-LED-0280-S2

1/2.8" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj LED dioda 2, domet LED dioda do 30m;Integriran mikrofon, fixna optika, vidni ugao 2.8mm - 107°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR: 120dB, 12V DC/PoE ,Max 7.1W (12V DC, IR on), Micro SD Card (support max. 256 GB) Kuciste: metalno. Zastita IP67. IVS Analitika: Intrusion; tripwire.Dozna PFA130-E , Nosac PFA152-E.



FullColour

Model: IPC-HFW2239S-SA-LED-0280-S2

1/2.8" CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj LED dioda 1, domet LED dioda do 30m; fixna optika, vidni ugao 2.8mm - 107°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR: 120dB, 12V DC/PoE ,Max 7.1W (12V DC, IR on), Micro SD Card (support max. 256 GB)
Kuciste: metalno. Zastita IP67. IVS Analitika: Intrusion; tripwire.
Dozna PFA134 , Nosac PFA152-E.



Model: IPC-HFW2241T-AS-0280-S2 WizMind

1/2.8" STARVIS CMOS 2mpx cip, 1080P (1920×1080), 2MP
broj dioda 4, domet dioda do 80m; Fixna optika, vidni ugao 106°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, WDR:120dB, 12V DC/PoE , Max 8.7W (12V DC, IR on), Micro SD Card (support max. 256 GB) Integriran mikrofon. Kuciste: metalno. Zastita IP67,IK10. Dozna PFA130-E , Nosac PFA152-E.



Model: ITC215-PW6M-IRLZF-B

AI IP bullet kamera za prepoznavanje registarskih tablica. 1/2.8" 2MP progressive scan CMOS.. IC LE diode dometa do 12m. Motorizovani zum objektiv 3.2-10.5mm F1.6-F3.3, automatski fokus, automatski (DC) iris. Podesivi vidni ugao 108.1°~ 30.3° horizontalno.Sa podrškom za detekciju i klasifikaciju vozila (veličina, boja, tip) i karakteristika osoba na prednjim sedištim. Snapshot registarske tablice, overview snapshot i snimanje. Ugrađena Bela lista sa do 10.000 unosa. Rele za kontrolu rampe/barijere. Ulaz za okidanje prepoznavanja induktivnom petljom.

IP VIDEO NADZOR 4MP



Model: **IPC-HFW1431S1-0280B**

1/3" CMOS 4mpx cip, 4MP (2688×1520),
broj dioda 12, domet dioda do 30m; Fixna optika, vidni ugao 106° Frame
Rate:2688 × 1520(1 fps-20 fps),2560 × 1440 (1 fps-25/30 fps),704 × 576 (1
fps-25 fps),704 × 480 (1 fps-30 fps), WDR: 120dB, 12V DC/PoE ,Max 7.5W
(12V DC, IR on), Micro SD Card (support max. 128 GB), Kuciste: Plastika.
Zastita IP67. IVS Analitika: Intrusion; tripwire.
Dozna PFA134, Nosac PFA152-E.



Model: **IPC-HDW1431S-0280B-S4**

1/3" CMOS 4mpx cip, 4MP (2688×1520),
broj dioda 12, domet dioda do 30m; Fixna optika, vidni ugao 106° Frame
Rate:2688 × 1520(1 fps-20 fps),2560 × 1440 (1 fps-25/30 fps),704 × 576 (1
fps-25 fps),704 × 480 (1 fps-30 fps), WDR: 120dB, 12V DC/PoE ,Max 7.5W
(12V DC, IR on), Micro SD Card (support max. 128 GB), Kuciste: metalno.
Zastita IP67. IVS Analitika: Intrusion; tripwire.
Dozna PFA130-E, Nosac PFA152-E.



Model: **IPC-HFW1431S-0280B-S4**

1/3" CMOS 4mpx cip, 4MP (2688×1520),
broj dioda 18, domet dioda do 30m; Fixna optika, vidni ugao 106° Frame
Rate:2688 × 1520(1 fps-20 fps),2560 × 1440 (1 fps-25/30 fps),704 × 576 (1
fps-25 fps),704 × 480 (1 fps-30 fps), WDR: 120dB, 12V DC/PoE ,Max 7.5W
(12V DC, IR on), Micro SD Card (support max. 128 GB), Kuciste: metalno.
Zastita IP67. IVS Analitika: Intrusion; tripwire.
Dozna PFA134, Nosac PFA152-E.



Model: **IPC-HDBW1435E-W-0280B**

1/3" CMOS 4mpx cip, 4MP (2688×1520),
broj dioda 24, domet dioda do 30m; Fixna optika, vidni ugao 106° Frame
Rate:2688 × 1520(1 fps-20 fps),2560 × 1440 (1 fps-25/30 fps),704 × 576 (1
fps-25 fps),704 × 480 (1 fps-30 fps), WDR: 120dB, 12V DC/PoE ,Max 7.5W
(12V DC, IR on), Micro SD Card (support max. 128 GB), Kuciste: metalno.
Zastita IP67, IK10. IVS Analitika: Intrusion; tripwire.
Dozna PFA136, Nosac PFA152-E.



Model: IPC-HFW1435S-W-0280B-S2

1/3" CMOS 4mpx cip, 4MP (2688×1520),
broj dioda 18, domet dioda do 30m; Fixna optika, vidni ugao 116° Frame
Rate:(2560 × 1440 @20 fps),(2304 × 1296 @25 fps), (2304 × 1296 @30 fps)
WDR: 120dB, 12V DC/PoE ,Max 7.5W (12V DC, IR on), Micro SD Card
(support max. 256 GB), Kuciste: metalno. Zastita IP67, IK10. IVS Analitika:
Intrusion; tripwire.
Dozna PFA134



Model: IPC-HDW2431T-AS-0280B-S2

1/3" CMOS 4mpx cip, 4MP (2688×1520),
broj dioda 2, domet dioda do 30m; Fixna optika, vidni ugao 102° Frame
Rate: 2688 × 1520(1 fps-20 fps),2560 × 1440 (1 fps-25/30 fps),704 × 576 (1
fps-25 fps),704 × 480 (1 fps-30 fps) WDR:120dB, 12V DC/PoE ,Max 6.6W
(12V DC, IR on), Micro SD Card (support max. 256 GB), Kuciste: metalno.
Zastita IP67, IK10. IVS Analitika: Intrusion; tripwire.
Dozna PFA134, Nosac PFA150.



Model: IPC-HFW2431S-S-0280B-S2

1/3" CMOS 4mpx cip, 4MP (2688×1520)
broj dioda 1, domet dioda do 30m; fixna optika, vidni ugao 2.8mm - 102°,
Frame Rate: 2688 × 1520 (1 fps-20 fps),
2560 × 1440 (1 fps-25/30 fps),704 × 576 (1 fps-25 fps),
704 × 480 (1 fps-30 fps) WDR: 120dB, 12V DC/PoE ,Max 5W (12V DC, IR on),
Micro SD Card (support max. 256 GB)
Kuciste: metalno. Zastita IP67. IVS Analitika: Intrusion; tripwire.
Dozna PFA134 , Nosac PFA152-E.



Model: IPC-HDW2431T-ZS

1/3" CMOS 4mpx cip, 4MP (2688×1520)
broj dioda 2, domet dioda do 40m; Motoriz. zoom 2.7 mm–13.5 mm, vidni
ugao 104°–27°, Frame Rate: 2688 × 1520 (1 fps-20 fps), 2560 × 1440 (1 fps-
25/30 fps),704 × 576 (1 fps-25 fps),
704 × 480 (1 fps-30 fps) WDR: 120dB, 12V DC/PoE ,Max 9.6W (12V DC, IR
on), Micro SD Card (support max. 256 GB)
Kuciste: metalno. Zastita IP67. IVS Analitika: Intrusion; tripwire.Dozna
PFA130-E , Nosac PFA152-E.



Model: IPC-HFW2431T-ZS

1/3" CMOS 4mpx cip, 4MP (2688×1520)
broj dioda 4, domet dioda do 60m; Motoriz. zoom 2.7 mm–13.5 mm, vidni ugao 104°–27°, Frame Rate: 2688 × 1520 (1 fps-20 fps), 2560 × 1440 (1 fps-25/30 fps), 704 × 576 (1 fps-25 fps), 704 × 480 (1 fps-30 fps) WDR: 120dB, 12V DC/PoE ,Max 9.6W (12V DC, IR on), Micro SD Card (support max. 256 GB)
Kuciste: metalno. Zastita IP67. IVS Analitika: Intrusion; tripwire.
Dozna PFA130-E , Nosac PFA152-E.



Model: IPC-HDW2439T-AS-LED-0208

1/3" CMOS 4mpx cip, 4MP (2688×1520)
broj dioda 2, domet dioda do 30m; Fiksna optika, vidni ugao 104°, Frame Rate: 2688 × 1520 (1 fps-20 fps), 2560 × 1440 (1 fps-25/30 fps), 704 × 576 (1 fps-25 fps), 704 × 480 (1 fps-30 fps) WDR: 120dB, 12V DC/PoE ,Max 9.6W (12V DC, IR on), Micro SD Card (support max. 256 GB)
Kuciste: metalno. Zastita IP67. IVS Analitika: Intrusion; tripwire. Integrisan mikrofon, Dozna PFA130E



Model: IPC-HFW2439S-SA-LED-0208

1/3" CMOS 4mpx cip, 4MP (2688×1520)
broj dioda 1, domet dioda do 30m; Fiksna optika , vidni ugao 104°, Frame Rate: 2688 × 1520 (1 fps-20 fps), 2560 × 1440 (1 fps-25/30 fps), 704 × 576 (1 fps-25 fps), 704 × 480 (1 fps-30 fps) WDR: 120dB, 12V DC/PoE ,Max 9.6W (12V DC, IR on), Micro SD Card (support max. 256 GB)
Kuciste: metalno. Zastita IP67. IVS Analitika: Intrusion; tripwire. Integrisan mikrofon, Dozna PFA134



Model: IPC-HDBW4431E-ASE-0360

1/3" CMOS 4mpx cip, 4MP (2688×1520)
broj dioda 18, domet dioda do 30m; Fixna optika, vidni ugao 83°, Frame Rate: Main Stream: 4M(1~25/30fps), Sub Stream: D1(1~25/30fps), Third Stream: 720P(1~25/30fps) WDR: 120dB, 12V DC/PoE ,Max 6W (12V DC, IR on), Micro SD Card (support max. 256 GB) Kuciste: metalno. Zastita IP67. IVS Dozna PFA203W, PFA152-E



Model: IPC-HFW4431E-SE-0360

1/3" CMOS 4mpx cip, 4MP (2688×1520)

broj dioda 2, doimet dioda do 40m; Fixna optika, vidni ugao 83° , Frame Rate: Main Stream: 4M(1~25/30fps),Sub Stream: D1(1~25/30fps),Third Stream: 720P(1~25/30fps) WDR: 120dB, 12V DC/PoE ,Max 6W (12V DC, IR on), Micro SD Card (support max. 256 GB)Kuciste: metalno. Zastita IP67. IVS Analitika: Intrusion; tripwire.

Dozna PFA121 , Nosac PFA152-E.



Model: IPC-HDBW4431F-AS-0360/0280

1/3" CMOS 4mpx cip, 4MP (2688×1520)

broj dioda 10, doimet dioda do 20m; fixna optika, vidni ugao 3.6mm- 87°/ 2.8mm - 104° , Integrisan mikrofon, Frame Rate:Main Stream: 4M(1~25/30fps), Sub Stream: D1(1~25/30fps), Third Stream: 720P(1~25/30fps), WDR: 120dB, 12V DC/PoE ,Max 4.5W (12V DC, IR on), Micro SD Card (support max. 256 GB)

Kuciste: metalno. Zastita IP67, IK10. IVS Analitika: Intrusion; tripwire, detekcija lica.

Dozna PFA139.



Model:TPC-BF1241-D3F4 Termalna kamera

1/2.7" progressive scan CMOS, 4MP (2336 × 1752)

vidno polje H: 50.6° , V: 37.8° , doimet dioda do 30m.Detektor Vanadium Oxide Uncooled FPA.Kuciste: metalno. Zastita IP67, IK10. IVS Analitika: Fire Detection & Alarm,Cold & Hot Spot Trace,Human & Vehicle Classification,Smoking Detection,Call Detection .Micro SD card (256 G) Napajanje Max: < 14 W .IP67 zastita.Dozna PFA 130-E,nosac PFA152-E.

IP VIDEO NADZOR 5MP



Model: IPC-HDBW2531E-S-0360/0280-S2

1/2.7" CMOS 5mpx cip, 5MP (2592×1944),

broj dioda 3, doimet dioda do 30m; Fixna optika, vidni ugao 3.6mm- 103°/2.8mm-84° , Frame Rate: Main stream:2592 × 1944 (1 fps-20 fps),2688 × 1520 (1 fps-25/30 fps), Sub stream:704 × 576 (1 fps-25 fps),704 × 480 (1 fps-30 fps) WDR:120dB, 12V DC/PoE ,Max 6.1W (12V DC, IR on), Micro SD Card (support max. 256 GB), Kuciste: metalno. Zastita IP67, IK10. IVS Analitika: Intrusion; tripwire.

Dozna PFA136, Nosac PFB203W.



Model: IPC-HFW2531T-AS-0360B

1/2.7" CMOS 5mpx cip, 5MP (2592×1944), broj dioda 4, domet dioda do 80m; Fixna optika, vidni ugao 3.6mm- 103°, Frame Rate: Main stream:2592 × 1944 (1 fps-20 fps),2688 × 1520 (1 fps-25/30 fps), Sub stream:704 × 576 (1 fps-25 fps),704 × 480 (1 fps-30 fps) WDR:120dB, 12V DC/PoE ,Max 6.1W (12V DC, IR on), Micro SD Card (support max. 256 GB), Kuciste: metal. Zastita IP67, IK10. IVS Analitika: Intrusion; tripwire.Nosac PFA 152-E,dozna PFA130-E



Model: IPC-HDW2531T-AS-S2

1/2.7" CMOS 5mpx cip, 5MP (2592×1944), broj dioda 2, domet dioda do 30m; Fixna optika, vidni ugao 3.6mm- 103°/2.8mm-84°, Frame Rate: Main stream:2592 × 1944 (1 fps-20 fps),2688 × 1520 (1 fps-25/30 fps), Sub stream:704 × 576 (1 fps-25 fps),704 × 480 (1 fps-30 fps) WDR:120dB, 12V DC/PoE ,Max 6.1W (12V DC, IR on), Micro SD Card (support max. 256 GB), Kuciste: metal+plastika. Zastita IP67, IK10. IVS Analitika: Intrusion; tripwire.Nosac PFA 152-E



Model: IPC-HFW2531S-S-0360/0280-S2

1/2.7" CMOS 5mpx cip, 5MP (2592×1944), broj dioda 1, domet dioda do 30m; Fixna optika, vidni ugao 3.6mm- 103°/2.8mm-84°, Frame Rate: Main stream:2592 × 1944 (1 fps-20 fps),2688 × 1520 (1 fps-25/30 fps), Sub stream:704 × 576 (1 fps-25 fps),704 × 480 (1 fps-30 fps) WDR:120dB, 12V DC/PoE ,Max 5.6W (12V DC, IR on), Micro SD Card (support max. 256 GB), Kuciste: metalno. Zastita IP67. IVS Analitika: Intrusion; tripwire. Dozna PFA134, Nosac PFA-152-E.



Model: IPC-HDBW2531R-ZS-S2

1/2.7" CMOS 5mpx cip, 5MP (2592×1944), broj dioda 2, domet dioda do 40m; Motoriz.zoom 2.7-13.5mm, vidni ugao 100°-26°, Frame Rate: Main stream:2592 × 1944 (1 fps-20 fps),2688 × 1520 (1 fps-25/30 fps), Sub stream:704 × 576 (1 fps-25 fps),704 × 480 (1 fps-30 fps) WDR:120dB, 12VDC/PoE ,Max 7.9W (12V DC, IR on), Micro SD Card (support max. 256 GB), Kuciste: metalno. Zastita IP67, IK10. IVS Analitika: Intrusion; tripwire. Dozna PFA137, Nosac PFB203W.



Model: IPC-HFW2531T-ZS-S2

1/2.7" CMOS 5mpx cip, 5MP (2592×1944),
broj dioda 4, domet dioda do 60m; Motoriz.zoom 2.7-13.5mm, vidni ugao
100°–26°, Frame Rate: Main stream:2592 × 1944 (1 fps-20 fps),2688 × 1520
(1 fps-25/30 fps), Sub stream:704 × 576 (1 fps-25 fps),704 × 480 (1 fps-30
fps) WDR:120dB, 12VDC/PoE ,Max 9.9W (12V DC, IR on), Micro SD Card
(support max. 256 GB), Kuciste: metalno. Zastita IP67, IVS Analitika:
Intrusion; tripwire.
Dozna PFA130-E, Nosac PFA152-E.



Model: IPC-HDW2531T-ZS-S2

1/2.7" CMOS 5mpx cip, 5MP (2592×1944),
broj dioda 2, domet dioda do 40m; Motoriz.zoom 2.7-13.5mm, vidni ugao
100°–26°, Frame Rate: Main stream:2592 × 1944 (1 fps-20 fps),2688 × 1520
(1 fps-25/30 fps), Sub stream:704 × 576 (1 fps-25 fps),704 × 480 (1 fps-30
fps) WDR:120dB, 12VDC/PoE ,Max 9.9W (12V DC, IR on), Micro SD Card
(support max. 256 GB), Kuciste: metalno. Zastita IP67, IVS Analitika:
Intrusion; tripwire.
Dozna PFA130-E, Nosac PFA152-E.



Model: IPC-HDW3549TM-AS-LED-0280B

1/2.7" CMOS 5mpx cip, 5MP (2592×1944),
broj dioda 2, domet dioda do 30m; fiksna optika, vidni ugao 100°–26°,
Frame Rate: Main stream:2592 × 1944 (1 fps-20 fps),2688 × 1520 (1 fps-
25/30 fps), Sub stream:704 × 576 (1 fps-25 fps),704 × 480 (1 fps-30 fps)
WDR:120dB, 12VDC/PoE ,Max 9.9W (12V DC, IR on), Kuciste: metalno.
Zastita IP67, IVS Analitika: Intrusion; tripwire.
Dozna PFA130-E, Nosac PFA152-E.



Model: IPC-HFW3549E-AS-LED-0280B

1/2.7" CMOS 5mpx cip, 5MP (2592×1944),
broj dioda 1, domet dioda do 30m; fiksna optika, vidni ugao 100°–26°,
Frame Rate: Main stream:2592 × 1944 (1 fps-20 fps),2688 × 1520 (1 fps-
25/30 fps), Sub stream:704 × 576 (1 fps-25 fps),704 × 480 (1 fps-30 fps)
WDR:120dB, 12VDC/PoE ,Max 9.9W (12V DC, IR on), Kuciste: metalno.
Zastita IP67, IVS Analitika: Intrusion; tripwire.
Dozna PFA134, Nosac PFA152-E.





Model: IPC-HDW5541TM-ASE-0280B

1/2.7" CMOS 5mpx cip, 5MP (2592×1944), broj dioda 2, dometa dioda do 50m; Fixna optika, vidni ugao 102°, Frame Rate: 20 fps@2592 × 1944, 50/60 fps@1080P (1920 × 1080), WDR:120dB, 12V DC/PoE , Max 9.5W (12V DC, IR on), Micro SD Card (support max. 256 GB) Integriran mikrofoni. Kuciste: metalno. Zastita IP67. Nosac PFA152-E, PFA151.



Model: IPC-HFW5541T-ASE-0280-S2 WizMind

1/2.7" CMOS 5mpx cip, 5MP (2592×1944), broj dioda 4, dometa dioda do 80m; Fixna optika, vidni ugao 102°, Frame Rate: 20 fps@2592 × 1944, 50/60 fps@1080P (1920 × 1080), WDR:120dB, 12V DC/PoE , Max 9.5W (12V DC, IR on), Micro SD Card (support max. 256 GB) Integriran mikrofoni. Kuciste: metalno. Zastita IP67,IK10. Dozna PFA130-E , Nosac PFA152-E, PFA151.



Model: IPC-HFW5541E-ZE

1/2.7" CMOS 5mpx cip, 5MP (2592×1944), broj dioda 4, dometa dioda do 50m; Motoriz.vari-focal 2.7 mm–13.5 mm, vidni ugao 100°, Frame Rate: 20 fps@2592 × 1944, 50/60 fps@1080P (1920 × 1080), WDR:120dB, 12V DC/PoE , Max 9.5W (12V DC, IR on), Micro SD Card (support max. 256 GB). Kuciste: metalno-plastika. Zastita IP67,IK10. Dozna PFA121,PFA152-E

IP VIDEO NADZOR 6MP

Model: **IPC-HFW4631E-SE-0280B**



1/2.9" CMOS 6mpx cip, 6MP (3072x 2048), broj dioda 2, domet dioda do 40m; Fixna optika, vidni ugao 98° , Frame Rate: Main Stream: 6MP (1~20fps), 4MP(1~25/30fps), Sub Stream: D1(1~25/30fps), Third Stream: 1080P(1~25/30fps)WDR: 120dB, 12V DC/PoE ,Max 6W (12V DC, IR on), Micro SD Card (support max. 256 GB)Kuciste: metalno. Zastita IP67. IVS Analitika: Intrusion; tripwire. Dozna PFA121 , Nosac PFA152-E.

Model: **IPC-HFW5631E-ZE**



1/2.9" STARVIS CMOS 6mpx cip, 6MP (3072x 2048), broj dioda 4, domet dioda do 50m; Motoriz.zoom 2.7mm ~13.5mm, Vidni ugao: H:91°~27° , V:58°~18° , Frame Rate: 20fps@6M(3072×2048),25/30fps@4M(2688×1520), WDR: 120dB, 12V DC/PoE , Max 12.95W (12V DC, IR on), Micro SD Card (support max. 256 GB) Kuciste: metalno. Zastita IP67. IVS Analitika: Intrusion; tripwire. Dozna PFA121 , Nosac PFA152-E.

IP PTZ KAMERE



Model: **SD22404T-GN**

1/3" 4 mpx CMOS, 2592(H) x 1520(V), 4X opticki zoom, optika 2.7mm~11mm, vidni ugao 112.5° ~ 30°. Sub stream1: D1/CIF(1 ~ 25/30fps), H.265/H.264: 448K ~ 8192Kbps. Main stream: 4M/3M/1080P/1.3M/720P (1~25/30fps). Napajanje DC 12V/1.5A, PoE(802.3af). Potrošnja 10W. Kuciste metalno. Zastita IP66, IK10. Nosac PFA137, PFB203W, PFA152-E



Starlight

Model: **SD50225U-HNI**

1/2.8" STARVIS CMOS 2mpx cip, 1080P(1920x1080), 25X opticki zoom, optika: 4.8mm~120mm; vidni ugao 62.8° ~ 2.6°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, OSD meni, BLC / HLC / WDR(120dB), Napajanje: AC24V/1.5A(±10%); Potrošnja: 13W, 23W (Heater on), IVS: Tripwire, Intrusion, Abandoned/Missing, Kuciste: metalno. Zastita IP66, IK10. Nosac PFB300C, PFA150, PFA151.



Starlight

Model: **SD59225U-HNI**

1/2.8" STARVIS CMOS 2mpx cip, 1080P(1920x1080), 25X opticki zoom, broj dioda 4, domet dioda do 150m; optika: 4.8mm~120mm; vidni ugao 62.8° ~ 2.6°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, OSD meni, BLC / HLC / WDR(120dB), Napajanje: AC24V/3A(±10%); Potrošnja: 13W, 23W (IR on), IVS: Tripwire, Intrusion, Abandoned/Missing, Kuciste: metalno. Zastita IP66, IK10. Nosac PFB300C, PFA150, PFA151.



Starlight

Model: **SD50230U-HNI**

1/2.8" STARVIS CMOS 2mpx cip, 1080P(1920x1080), 25X opticki zoom, optika: 4.5mm~135mm; vidni ugao 67.8° ~ 2.4°, Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P, OSD meni, BLC / HLC / WDR(120dB), Napajanje: AC24V/1.5A(±10%); Potrošnja: 13W, 23W (Heater on), IVS: Tripwire, Intrusion, Abandoned/Missing, Kuciste: metalno. Zastita IP66, IK10. Nosac PFB300C, PFA150, PFA151.



Wiz Sense

Model: **SD5A432XA-HNR**

1/2.8" STARVIS CMOS 4mpx cip, (2560x1440), 32X opticki zoom, optika: 4.5mm~135mm; vidni ugao 61.6° ~ 2.1°, Frame Rate: 4M/3M/1080P/1.3M/720P (1~25/30 fps, D1/CIF (1~25/30 fps), BLC / HLC / WDR(120dB), Napajanje: AC 24V/3A ± 25%; Potrošnja: 12W, 20W, Kuciste: metalno. Zastita IP67, IK10. Nosac PFB300C, PFA150, PFA151.



Wiz Sense

Starlight

Model: **SD65F233XA-HNR**

1/1.8" STARVIS CMOS 2mpx cip,(2560×1440), 33X opticki zoom, optika:5.8 mm–191.4 mm ; vidni ugao 60.1°–3.2°; V: 35.3°–1.8°; D: 67.9°–3.7°,FrameRate:1080P/1.3M/720P (1–50/60fps),BLC / HLC / WDR(120dB), Napajanje:AC24V/3A±25%
PoE+ (802.3at); Potrošnja: 12W,20W , Kuciste: metalno. Zastita IP67, IK10.
Nosac PFB300C, PFA140, PFA150,PFA120



Starlight

Model: **SD49225XA-HNR**

1/2.8" STARVIS CMOS 2mpx cip, 1080P(1920×1080), 25X opticki zoom, broj dioda 6, dolet dioda do 100m; optika: 4.8mm~120mm; vidni ugao 62.8° ~ 2.6°, Frame Rate:25/30fps@1080P, 25/30/50/60fps@720P,OSD meni,BLC / HLC / WDR(120dB), Napajanje: AC24V/3A(±10%); Potrošnja: 13W,22W (IR on), IVS: Tripwire, Intrusion, Abandoned/Missing, Kuciste: metalno. Zastita IP66, IK10.
Nosac PFB300C, PFA150, PFA151.



Starlight

Model: **SD50230U-HNI**

1/2.8" STARVIS CMOS 2mpx cip, 1080P(1920×1080), 25X opticki zoom, optika: 4.5mm~135mm; vidni ugao 67.8° ~ 2.4°, Frame Rate:25/30fps@1080P, 25/30/50/60fps@720P,OSD meni,BLC / HLC / WDR(120dB), Napajanje: AC24V/1.5A(±10%); Potrošnja: 13W,23W (Heater on), IVS: Tripwire, Intrusion, Abandoned/Missing, Kuciste: metalno. Zastita IP66, IK10.
Nosac PFB300C, PFA150, PFA151.

MREZNI SNIMACI

Model: **NVR4104HS-4KS2**

4ch Mrežni snimac, Kompresija: H.265+/H.265/H.264+/H.264; Rezolucija snimanja : 8Mp/ 6Mp/ 5MP/ 4MP/ 3MP/ 1080P/ 1.3MP/ 720P etc.; 1 HDMI ,1 VGA; Rezolucija prikaza: HDMI: 3840×2160, 1920×1080, 1280×1024, 1280×720, VGA: 1920×1080, 1280×1024, 1280×720 1 audio ulaz, 1 audio izlaz; audio preko koaksijalnog kabla; 1HDD do 6TB; Napajanje DC12V/2A, Potrošnja: 6.3W (Without HDD)



Model: **NVR4104HS-4KS2/L**

4ch Mrežni snimac, New 4.0 user interface, Security baseline 2.1 Kompresija: H.265+/H.265/H.264+/H.264; Rezolucija snimanja : 8Mp/ 6Mp/ 5MP/ 4MP/ 3MP/ 1080P/ 1.3MP/ 720P etc.; 1 HDMI ,1 VGA; Rezolucija prikaza: HDMI: 3840×2160, 1920×1080, 1280×1024, 1280×720, VGA: 1920×1080, 1280×1024, 1280×720 1 audio ulaz, 1 audio izlaz; audio preko koaksijalnog kabla; 1HDD do 10TB; Napajanje DC12V/2A, Potrošnja: 6.3W (Without HDD)



Model: **NVR4108HS-4KS2/L**

8ch Mrežni snimac, New 4.0 user interface, Security baseline 2.1 Kompresija: H.265+/H.265/H.264+/H.264; Rezolucija snimanja : 8Mp/ 6Mp/ 5MP/ 4MP/ 3MP/ 1080P/ 1.3MP/ 720P etc.; 1 HDMI ,1 VGA; Rezolucija prikaza: HDMI: 3840×2160, 1920×1080, 1280×1024, 1280×720, VGA: 1920×1080, 1280×1024, 1280×720 1 audio ulaz, 1 audio izlaz; audio preko koaksijalnog kabla; 1HDD do 10TB; Napajanje DC12V/2A, Potrošnja: 6.3W (Without HDD)



Model: **NVR4108HS-4KS2**

8ch Mrežni snimac, Kompresija: H.265+/H.265/H.264+/H.264; Rezolucija snimanja : 8Mp/ 6Mp/ 5MP/ 4MP/ 3MP/ 1080P/ 1.3MP/ 720P etc.; 1 HDMI ,1 VGA; Rezolucija prikaza: HDMI: 3840×2160, 1920×1080, 1280×1024, 1280×720, VGA: 1920×1080, 1280×1024, 1280×720 1 audio ulaz, 1 audio izlaz; audio preko koaksijalnog kabla; 1HDD do 6TB; Napajanje DC12V/2A, Potrošnja: 6.3W (Without HDD)



Model: **NVR4116HS-4KS2**

16ch Mrežni snimac, Kompresija: H.265+/H.265/H.264+/H.264; Rezolucija snimanja : 8Mp/ 6Mp/ 5MP/ 4MP/ 3MP/ 1080P/ 1.3MP/ 720P etc.; 1 HDMI ,1 VGA; Rezolucija prikaza: HDMI: 3840×2160, 1920×1080, 1280×1024, 1280×720, VGA: 1920×1080, 1280×1024, 1280×720 1 audio ulaz, 1 audio izlaz; audio preko koaksijalnog kabla; 1HDD do 6TB; Napajanje DC12V/2A, Potrošnja: 6.3W (Without HDD)





Model: NVR4116HS-4KS2/L

16ch Mrežni snimac, Kompresija: H.265+/H.265/H.264+/H.264; Rezolucija snimanja : 8Mp/ 6Mp/ 5MP/ 4MP/ 3MP/ 1080P/ 1.3MP/ 720P etc.; 1 HDMI ,1 VGA; Rezolucija prikaza: HDMI: 3840×2160, 1920×1080, 1280×1024, 1280×720, VGA: 1920×1080, 1280×1024, 1280×720 1audio ulaz, 1 audio izlaz; audio preko koaksijalnog kabla; 1HDD do 6TB; Napajanje DC12V/2A, Potrošnja: 6.3W (Without HDD)



Model: NVR4208-4KS2

8ch Mrežni snimac, Kompresija: H.265+/H.265/H.264+/H.264; Rezolucija snimanja : 8Mp/ 6Mp/ 5MP/ 4MP/ 3MP/ 1080P/ 1.3MP/ 720P etc.; 1 HDMI ,1 VGA; Rezolucija prikaza: HDMI: 3840×2160, 1920×1080, 1280×1024, 1280×720, VGA: 1920×1080, 1280×1024, 1280×720 1audio ulaz, 1 audio izlaz; audio preko koaksijalnog kabla; 1HDD do 6TB; Napajanje DC12V/2A, Potrošnja: 2 SATA , 6.9W (Without HDD)



Model: NVR4208-8P-4KS2

8ch Mrežni snimac, Kompresija: H.265+/H.265/H.264+/H.264; Rezolucija snimanja : 8Mp/ 6Mp/ 5MP/ 4MP/ 3MP/ 1080P/ 1.3MP/ 720P etc.; 1 HDMI ,1 VGA; Rezolucija prikaza: HDMI: 3840×2160, 1920×1080, 1280×1024, 1280×720, VGA: 1920×1080, 1280×1024, 1280×720 1audio ulaz, 1 audio izlaz; audio preko koaksijalnog kabla; 2HDD do 10TB; Napajanje DC12V/2A, Potrošnja: 2 SATA , 6.9W (Without HDD)



Model: NVR4216-4KS2

16ch Mrežni snimac, Kompresija: H.265+/H.265/H.264+/H.264; Rezolucija snimanja : 8Mp/ 6Mp/ 5MP/ 4MP/ 3MP/ 1080P/ 1.3MP/ 720P etc.; 1 HDMI ,1 VGA; Rezolucija prikaza: HDMI: 3840×2160, 1920×1080, 1280×1024, 1280×720, VGA: 1920×1080, 1280×1024, 1280×720 1audio ulaz, 1 audio izlaz; audio preko koaksijalnog kabla; 1HDD do 6TB; Napajanje DC12V/2A, Potrošnja: 2 SATA , 6.9W (Without HDD)



Model: NVR4216-4KS2/L

16 -kanalni 1U 2HDD mrežni video rekorder
Novi 4.0 korisnički interfejs, Sigurnosna osnova 2.1
H.264, H.265, Smart H.264+i Smart H.265+. Automatski prekidač H.265.Maks. mogućnost dekodiranja: 8 × 1080p@30 fps. Podržava adaptivno dekodiranje.Podržava mainstream kamere ONVIF i RTSP protokola.P2P daljinski nadzor, video reprodukcija na mobilnom uređaju.VGA/HDMI istovremeni video izlaz, maksimalna rezolucija HDMI -a je 4K.
AI kamerom: Otkrivanje lica, zaštita perimetra, IVS, brojanje ljudi, toplotna mapa i SMD



Model: NVR4216-16P-4KS2

16ch Mrezni snimac, Kompresija: H.265+/H.265/H.264+/H.264; Rezolucija snimanja : 8Mp/ 6Mp/ 5MP/ 4MP/ 3MP/ 1080P/ 1.3MP/ 720P etc.; 1 HDMI ,1 VGA; Rezolucija prikaza: HDMI: 3840×2160, 1920×1080, 1280×1024, 1280×720, VGA: 1920×1080, 1280×1024, 1280×720 1audio ulaz, 1 audio izlaz; audio preko koaksijalnog kabla; 2HDD do 10TB; Napajanje DC12V/2A, Potrošnja: 2 SATA , 6.9W (Without HDD)



Model: NVR4232-4KS2/L

32ch Mrezni snimac, New 4.0 user interface, Security baseline 2.1 Kompresija: H.265+/H.265/H.264+/H.264; Rezolucija snimanja : 8Mp/ 6Mp/ 5MP/ 4MP/ 3MP/ 1080P/ 1.3MP/ 720P etc.; 1 HDMI ,1 VGA; Rezolucija prikaza: HDMI: 3840×2160, 1920×1080, 1280×1024, 1280×720, VGA: 1920×1080, 1280×1024, 1280×720, 1audio ulaz, 1 audio izlaz; ; 2HDD do 10TB; Napajanje DC12V/4A, Potrošnja: 2 SATA , 6.9W (Without HDD)



Model: NVR4232-4KS2

32ch Mrezni snimac, Kompresija: H.265+/H.265/H.264+/H.264; Rezolucija snimanja : 8Mp/ 6Mp/ 5MP/ 4MP/ 3MP/ 1080P/ 1.3MP/ 720P etc.; 1 HDMI ,1 VGA; Rezolucija prikaza: HDMI: 3840×2160, 1920×1080, 1280×1024, 1280×720, VGA: 1920×1080, 1280×1024, 1280×720, 1audio ulaz, 1 audio izlaz; ; 2HDD do 6TB; Napajanje DC12V/4A, Potrošnja: 2 SATA , 6.9W (Without HDD)



Model: NVR4416-16P-4KS2

16ch Mrezni snimac, Kompresija: H.265+/H.265/H.264+/H.264; Rezolucija snimanja : 8Mp/ 6Mp/ 5MP/ 4MP/ 3MP/ 1080P/ 1.3MP/ 720P etc.; 1 HDMI ,1 VGA; Rezolucija prikaza: HDMI: 3840×2160, 1920×1080, 1280×1024, 1280×720, VGA: 1920×1080, 1280×1024, 1280×720, 1audio ulaz, 1 audio izlaz; ;Local HDD and network.4HDD do 10TB.Napajanje 100V–240V AC, 50 Hz–60 Hz



Model: NVR5208-4KS2

8ch Mrezni snimac, Kompresija: H.265+/H.265/H.264+/H.264; Rezolucija snimanja : 12MP with 15fps, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 1.3MP, 720P, D1, CIF with 30fps; 1 HDMI ,1 VGA; Rezolucija prikaza: HDMI: 3840 × 2160 , 1920 × 1080 , 1280 × 1024,1280 × 720 , 1024 × 768, VGA: 1920 × 1080 , 1280 × 1024, 1280 × 720 , 1024 × 768, 1audio ulaz, 1 audio izlaz; ; 2HDD do 10TB; Napajanje DC12V/4A,



Model: NVR5208-8P-4KS2

8ch Mrežni snimac, Kompresija: H.265+/H.265/H.264+/H.264; Rezolucija snimanja : 12MP with 15fps, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 1.3MP, 720P, D1, CIF with 30fps; 1 HDMI ,1 VGA; Rezolucija prikaza: HDMI: 3840 × 2160 , 1920 × 1080 , 1280 × 1024,1280 × 720 , 1024 × 768, VGA: 1920 × 1080 , 1280 × 1024, 1280 × 720 , 1024 × 768, 1 audio ulaz, 1 audio izlaz; ; 2HDD do 10TB; Napajanje DC12V/4A,



Model: NVR5216-4KS2

16ch Mrežni snimac, Kompresija: H.265+/H.265/H.264+/H.264; Rezolucija snimanja : 12MP with 15fps, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 1.3MP, 720P, D1, CIF with 30fps; 1 HDMI ,1 VGA; Rezolucija prikaza: HDMI: 3840 × 2160 , 1920 × 1080 , 1280 × 1024,1280 × 720 , 1024 × 768, VGA: 1920 × 1080 , 1280 × 1024, 1280 × 720 , 1024 × 768, 1 audio ulaz, 1 audio izlaz; ; 2HDD do 10TB; Napajanje DC12V/4A,



Model: NVR5232-4KS2

32ch Mrežni snimac, Kompresija: H.265+/H.265/H.264+/H.264; Rezolucija snimanja : 12MP with 15fps, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 1.3MP, 720P, D1, CIF with 30fps.; 1 HDMI ,1 VGA; Rezolucija prikaza: HDMI: 3840 × 2160 , 1920 × 1080 , 1280 × 1024,1280 × 720 , 1024 × 768, VGA: 1920 × 1080 , 1280 × 1024, 1280 × 720 , 1024 × 768, 1 audio ulaz, 1 audio izlaz; ; 2HDD do 10TB; Napajanje DC12V/4A, Potrošnja: 2 SATA , 9.5W (Without HDD)



Model: NVR5432-4KS2

32ch Mrežni snimac, Kompresija: H.265+/H.265/H.264+/H.264; Rezolucija snimanja : 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 1.3MP, 720P, D1 etc.; 2 HDMI ,2 VGA; Rezolucija prikaza: HDMI1: 3840 × 2160 , 1920 × 1080 , 1280 × 1024,1280 × 720 , 1024 × 768, VGA1: 1920 × 1080 , 1280 × 1024, 1280 × 720 , 1024 × 768, HDMI2/VGA2: 1920 × 1080, 1 audio ulaz, 2 audio izlaz; ; 2HDD do 10TB; Napajanje DC12V/4A, Potrošnja: 4 SATA , 16.7W (Without HDD)



Model: NVR5432-16P-4KS2E



32ch Mrezni snimac, Kompresija: H.265+/H.265/H.264+/H.264; Rezolucija snimanja : 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 1.3MP, 720P, D1 etc.; 2 HDMI ,2 VGA; Rezolucija prikaza: HDMI1: 3840 × 2160 , 1920 × 1080 , 1280 × 1024,1280 × 720 , 1024 × 768, VGA1: 1920 × 1080 , 1280 × 1024, 1280 × 720 , 1024 × 768, HDMI2/VGA2: 1920 × 1080, PoE portovi: 16 ports (IEEE802.3af/at), 1audio ulaz, 1 audio izlaz; ; 2HDD do 10TB; Napajanje DC12V/4A, Potrošnja: 4 SATA , 17.5W (Without HDD)



Model: NVR5464-4KS2

32ch Mrezni snimac, Kompresija: H.265+/H.265/H.264+/H.264; Rezolucija snimanja : 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 1.3MP, 720P, D1 etc.; 2 HDMI ,2 VGA; Rezolucija prikaza: HDMI1: 3840 × 2160 , 1920 × 1080 , 1280 × 1024,1280 × 720 , 1024 × 768, VGA1: 1920 × 1080 , 1280 × 1024, 1280 × 720 , 1024 × 768, HDMI2/VGA2: 1920 × 1080, 1audio ulaz, 2 audio izlaz; ; 4HDD do 10TB; Napajanje DC12V/4A, Potrošnja: 4 SATA , 16.7W (Without HDD)



SLIKA	OPIS
SWITCHEVI	
	<p>PFS3005-5ET-L 5-Port Desktop Switch (Neupravljiv) Layer dva komercijalni switch Ethernet Port rate:100 Mbps Total:IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE802.3az supply:5V/500mA DC, Dimenzije:77mmx46mmx21mm Weight:200gr</p>
	<p>PFS3008-8ET-L 8-Port Desktop Ethernet Switch (Neupravljiv) Layer dva komercijalni switch Ethernet Port rate:100 Mbps Total-IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE802.3x supply:5V/500mA DC, Dimenzije:125mmx65mmx22mm, Weight:400gr</p>
	<p>PFS3005-5GT-L 5-Port Desktop Gigabit Ethernet Switch (Neupravljiv) Layer dva komercijalni switch Ethernet Port rate: 1 Gbps Total:IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE802.3x supply:5V/1A DC,Dimenzija: 125mmx65mmx22mm Weight:200gr</p>
	<p>PFS3008-8GT-L 8-Port Desktop Gigabit Ethernet Switch (Neupravljiv) Layer dva komercijalni switch Ethernet Port rate: 1 Gbps Total-IEEE 802.3i, IEEE 802.3u, IEEE802.3ab, IEEE802.3x supply:5V/1A DC, Dimenzije:125mmx65mmx22mm, Weight:400gr</p>
POE SWITCHEVI	
	<p>PFS3005-4P-58 4-Port PoE Switch (Neupravljiv) Layer dva komercijalni switch 1*10/100 Base-T, 4*10/100 Base-T, (PoE napajanje), svaki izlaz ≤30W, Ukupno ≤58W, PoE protocol: IEEE802.3af, IEEE802.3at, Ispravljač 51VDC, Radna temperatura: -10°C~50°C, Dimenzije: 100mmx100mmx26mm</p>

**PFS3005-4ET-60-V2**

5-Port Unmanaged Desktop Switch sa 4-Port PoE

Layer dva komercijalni switch, Intelligent PoE

1*10/100 Base-T, 4*10/100 Base-T, (PoE napajanje), svaki izlaz ≤30W, Ukupno ≤58W, PoE protocol: IEEE802.3, IEEE802.3u, IEEE802.3x, Ispravljač 51VDC, Radna temperatura: -10°C~55°C, Dimenzije: 130 mm × 85 mm × 26 mm

**PFS3006-4ET-60**

4-Port PoE Switch (Neupravljiv)

Layer dva komercijalni switch

2*10/100Mbps Uplink ports, **UPLINK**

4*10/100 Mbps PoE ports, Port1≤60W, IEEE802.3af (PoE), IEEE802.3at (PoE+), Hi-PoE, Port2-4≤30W, Total≤60W, dimenzije 130mm×85mm×26mm

**PFS3106-4ET-60**

4-Port PoE Switch (Neupravljiv)

Layer dva switch

1*10/100/1000 Mbps Uplink port, **SFP**

4*10/100Mbps POE portovi, 100/1000 SPF port,

Port1≤60W, IEEE802.3af (PoE), IEEE802.3at (PoE+), Hi-PoE, Port2-4≤30W, Total≤60W, dimenzije 130mm×85mm×26mm

**PFS3008-8GT-60**

8-Port Gigabitni Ethernet PoE Switch sa 4-Port PoE

Layer dva komercijalni switch

4x 10/100/1000M Base-T (PoE power supply, 4x10/100/1000M Base-T;

Port1≤60W, Port2-4≤30W, Total≤60W, IEEE802.3af/IEEE802.3at/Hi-PoE, Power supply:DC48~57V, Dimension: 190mm×100mm×30mm,

Weight: 480g

**PFS3009-8ET-96**

8-Port PoE Switch (Neupravljiv)

Layer dva komercijalni switch

8 x10/100M Base-T (PoE power supply)

1 x10/100M Base-T; Port1≤60W, Port2-8≤30W, Total≤96W

IEEE802.3af/IEEE802.3at/Hi-PoE, Power supply:DC48~57V

Dimension: 190mm×100mm×30mm

Weight: 480g

**PFS3110-8P-96**

8-Port PoE Switch

Layer dva industrijski PoE switch

1x1000 Base-X, 1x10/100/1000 Base-T,

8x10/100 Base-T (PoE power supply), IEEE 802.3af/802.3at(PoE+), Power

supply: DC53V, Each power ≤30W, Total≤93W, Dimension: 150 x100 x42mm,

Weight: 0.54kg

**PFS3110-8ET-96**

8-Port PoE Switch (neupravljiv)

Layer dva industrijski PoE switch

1x1000 Base-X, 1x10/100/1000 Base-T, **SFP**

8x10/100 Base-T (PoE power supply, Port1-2≤60W, Port3-8≤30W, Total≤96W,

Power supply: DC 48-57V, Dual power backup, Dimension: 150 x100 x42mm

Weight: 0.54kg

**PFS3010-8ET-96**

8-Port PoE Switch (neupravljiv)

Layer dva PoE switch

2*10/100/1000Mbps ports **UPLINK**

8*10/100Mbps PoE ports (Poe power consumption: Port1≤60W, Port2-8≤30W,

Total≤96W, Power supply: DC 48-57V, Dual power backup, Dimension:

190mm×100mm×30mm

Weight: 0.49kg

**PFS3206-4P-96**

4-Port PoE Switch(Neupravljiv).

Layer 2 unmanaged access switch.Ethernet Port 2*1000 Base-X.1*10/100/1000

Base-T(Hi-PoE/PoE+/PoE)

3*10/100 Base-T (PoE+/PoE) .Dimenzije 150mm×100mm×30mm

**PFS3016-16GT**

16-Port Gigabit Switch(Neupravljiv).

Layer 2 unmanaged access switch.Ethernet Port 16*10/100/1000 Base-

T.Napajanje AC:100-240V; 50/60Hz.Dimenzije 294mm x 178mm x 44mm.

**PFS3024-24GT**

24-Port Gigabit Switch(Neupravljiv).Layer 2 unmanaged access switch.Ethernet

Port 24*10/100/1000 Base-T.

Napajanje AC: 100-240V; 50/60Hz.Dimenzije 294mm x 178mm x 44mm.

**PFS3211-8GT-120**

11-Port Gigabit Switch with 8-Port PoE (Neupravljiv).Layer 2 Hardened PoE switch.
8*10/100/1000Mbps Base-T (PoE power supply)1*10/100/1000 Mbps Base-T
2*1000Mbps Base-X .Port1&5 ≤60W, Port2~4&Port6~8≤30W, Total
power≤120W.Dimenzije 150mm×110mm×42mm

**PFS3218-16ET-135**

16 portni switch Inteligentni PoE
PD Alive (PoE Vatchdog) \
PoE prenos na velike udaljenosti
Glatki prenos
Široka radna temperatura: -10 do 55 ° C (14 ° F do 131 ° F)
Izolacija portova.Dimenzije 440 mm × 300 mm × 44 mm

**PFS3226-24ET-240**

24 portni Inteligentni PoE
PD Alive (PoE Vatchdog)
PoE prenos na velike udaljenosti
Glatki prenos
Široka radna temperatura: -10 do 55 ° C (14 ° F do 131 ° F)
Izolacija portova.Dimenzije 440 mm × 300 mm × 44 mm

**PFS3220-16GT-240**

16-Port Gigabit Switch with Intelligent PoE.Svi Giga portovi. Red Port Supports BT
90W. 8*10/100/1000Mbps Base-T (PoE power supply)1*10/100/1000 Mbps Base-
T 2*1000Mbps .Port 1-2≤90W, Port 3-16≤30W, total≤240W, Total
power≤120W.Dimenzije 440 mm × 300 mm × 44 mm

**PFS4218-16ET-240**

16-Port PoE Switch
Layer 2 upravljivi PoE switch
Combo 1000BASE-T/SFP port x 2
10/100 Base-T x16 (Hi-PoE/PoE+/PoE)
IEEE802.3af/IEEE802.3at/Hi-PoE
'Orange port' support Hi-PoE, can be used with the PoE extender (PFT1300),
250m long distance PoE transmission
PoE budget : 240W
Dimension: 440mm x300mm x44mm

**PFS4226-24ET-360**

24-Port PoE Switch
Layer 2 upravljivi PoE switch
Combo 1000BASE-T/SFP port x 2
10/100 Base-T x24 (Hi-PoE/PoE+/PoE)
IEEE802.3af/IEEE802.3at/Hi-PoE
'Orange port' support Hi-PoE, can be used with the PoE extender (PFT1300),
250m long distance PoE transmission
PoE budget : 360W
Dimension: 440mm x300mm x44mm



PFS3228-24GT-360

24-Port PoE switch with red port supporting IEEE802.3bt standard. It supports maximum 90W IEEE802.3af, IEEE802.3at, Hi-PoE, IEEE802.3
Port 1–24: 24 × RJ45 10/100/1000 M (PoE)
Port 25–26: 2 × RJ45 10/100/1000 M (uplink)
Port 27–28: 2 × SFP 1000 M (uplink)
PoE budget : 360W
Dimension: 440 mm × 300 mm × 44 mm

MODULI ZA OPTIKU



PFT3950 Modul

1.25G 850nm 500m SFP
Mult-mode



PFT3960 Modul

1.25G; TX 1310nm,RX 1550nm; 20km; -40°C~85°C
Single-mode;
Single fiber bi-directional transmission



PFT3970 Modul

1.25G; TX 1550nm,RX 1310nm; 20km; -40°C~85°C;
Single-mode;
Single fiber bi-directional transmission



SLIKA

OPIS

KOMPLETI

KTA02 KOMPLET VIDEO INTERFONA

Komplet video interfona

7 "TFT ekran

Funkcija video interfona: Otključavanje, glasovni poziv, video poziv, podešavanje jačine zvuka

Kapacitet sistema: 2 stanice za vrata + 3 unutrašnja monitora

Više zvukova zvona

Podržava digitalni široki dinamički opseg (DVDR)



new

alhua
TECHNOLOGY

KTP01(F) KOMPLET VIDEO INTERFONA

Komplet sadrzi:

Pozivnu tablu ,DHI-VTO2202F,

Monitor: DHI-VTH2421FW-P,

Switch 4-porta: PFS3005-4ET-60,

Doznu: Alu.ugradnu doznu sa adapterom (VTM114)

2-Wire Inteface

7-inch TFT screen

IPC surveillance

Alarm integration

2-door control

Remote intercom with mobile APP(DMSS)



KIT



MONITORI



VTH5321GW-W

Android 7-inčni digitalni unutrašnji monitor
Android 8.1
Više korisničkog interfejsa
Ethernet i Vi-Fi
7 "TFT kapacitivni ekran osetljiv na dodir, 1024 × 600
Brza konfiguracija sistema vila



VTH1510CH

7" TFT otporni ekran osetljiv na dodir
IPC nadzor
Integracija alarma
Micro SD kartica opciona, maksimalno 32 GB
Snimanje i snimak (potrebna je SD kartica)



VTH1560BW Monitor Beli

IP unutrašnji monitor
7 "TFT kapacitivni ekran osetljiv na dodir
IPC nadzor
Integracija alarma
Ugrađena SD kartica od 8 GB
Snimanje i snimak



VTH2421FW-P Monitor Beli

7 "TFT kapacitivni ekran osetljiv na dodir, 1024 k 600
IPC nadzor
Integracija alarma
Visoke performanse i isplativost
Ugrađena SD kartica od 8 GB
Podržava standardni PoE



VTH5321GW-W Monitor

Android 7-inčni digitalni unutrašnji monitor
Android 8.1
Više korisničkog interfejsa prilagođenog korisnicima
Ethernet i Vi-Fi
7" TFT kapacitivni ekran osetljiv na dodir, 1024×600
Brza konfiguracija za sistem vila
SD Kartica je potrebna



VTH5221DW-S2 Monitor

Unutrašnji Vi-Fi monitor

7 "TFT kapacitivni ekran osetljiv na dodir, 1024k600

IPC nadzor

6ch žična integracija alarma, 6ch bežična integracija alarma (433MHZ)

Opcionalno Micro SD kartica, mak 32GB

Snimanje i snimak (potrebna SD kartica)

POZIVNE JEDINICE



VTO2211G-WP

IP Vila Vi-Fi Door Station

Tanki i lagani dizajn. -30 ° C do +60 ° C (-22 ° F do +140 ° F) radna temperatura. IP65

(potrebna je silikonska zaptivna masa. Za detalje pogledajte vodič za brzi početak.) IC

osvetljenje i noćni vid. Otključavanje kartice, otključavanje aplikacije i otključavanje

unutrašnjeg monitora. Dvosmerni audio i glasovni poziv putem aplikacije. Kapacitet

kartice: 10.000. Alarm protiv neovlašćenog pristupa. Standardni PoE

Kontrolišite dve brave. Podržava bežičnu mrežu



VTO1210B-X Pozivna tabla

HD CMOS CAMERA

Kamera rezolucije 1/2.7" 1.3MP CMOS

Vidni ugao D:95° H:75°, radna temperatura 40°C~+60°C.

Support Dual-way Bidirectional talk, Omnidirectional Mic I Built-in Speaker. Podržava

dvosmernu glasovnu komunikaciju I Mifare Card. IP65 zaštita. Internet protokol

TCP/IP. Kontrola za 1 vrata.



VTO6521H Pozivna tabla

HD CMOS CAMERA 4.3 inch IPS display 800x480

Kamera rezolucije 1/2.7" 2MP CMOS

Vidni ugao D:134.45° H:113.79°, radna temperatura -30°C~+60°C.

Support Dual-way Bidirectional talk, Omnidirectional Mic I Built-in Speaker. Podržava

dvosmernu glasovnu komunikaciju I Mifare Card.

Multiple unlock modes: Password unlock, IC card unlock, and remote unlock IP65

zaštita. Internet protokol TCP/IP. Kontrola za 1 vrata.



VTO1210C-X Pozivna tabla

HD CMOS CAMERA

Kamera rezolucije 1/2.7" 1.3MP CMOS

Vidni ugao D:95° H:75°, radna temperatura 40°C~+60°C.

Support Dual-way Bidirectional talk, Omnidirectional Mic I Built-in Speaker. Podržava dvosmernu glasovnu komunikaciju I Mifare Card. IP54, IK07. Internet protokol TCP/IP. Kontrola za 1 vrata.



VTO1220A Pozivna tabla

HD CMOS CAMERA

Kamera rezolucije 1/2.7" 1.3MP CMOS, 3.5" TFT 320x240

Vidni ugao D:95° H:75°, radna temperatura 40°C~+60°C.

Support Dual-way Bidirectional talk, Omnidirectional Mic I Built-in Speaker. Citac Mifare Card. IP54. Internet protokol TCP/IP. Kontrola za 1 vrata.



VTO1220BW Pozivna tabla

HD CMOS CAMERA

Kamera rezolucije 1/2.7" 1.3MP CMOS, 3.5" TFT 320x240

Vidni ugao D:95° H:75°, radna temperatura 40°C~+60°C.

Support Dual-way Bidirectional talk, Omnidirectional Mic I Built-in Speaker. Citac Mifare Card. IP65. Internet protokol TCP/IP. Kontrola za 1 vrata.



VTO2000A Pozivna tabla

HD CMOS CAMERA

Kamera rezolucije 1/2.7" 1.3MP CMOS,

Vidni ugao D:120° H:90°, radna temperatura 40°C~+60°C.

Support Dual-way Bidirectional talk, Omnidirectional Mic I Built-in Speaker. IP54, IK07. Internet protokol TCP/IP. Kontrola za 1 vrata.



VTO2000A-B Pozivna tabla

Modul sa tri tastera a za IP dahua modularni sistem, ispunjava IP54 i IK07 standard.

Ako se u sistemu nalazi DH-VTO2000A-R (ima proximity senzor) pločica sa imenom svetli na detekciju osobe, ako ne onda svetli na pritisak tastera. ☒



VTO2111D-P-S2

IP Villa Pozivni tablo

Kamera visoke rezolucije 1/4" 1MP CMOS high definition, low illumination/WDR, color/IR

Vidni ugao: Horizontal: 107°; vertical: 61°; diagonal: 122°

Radna temperatura -30°C–60°C, Zastita IP65 (Neophodna silikonska zastita, za detalje pogledati uputstvo.), Supports auto IR illumination and D/N, Card/app remote/indoor monitor unlock, Podrazava dvosmernu glasovnu komunikaciju-pozivanje; podrzava pozivanje izmedju tabloa i aplikacije. 10,000 kartica/tagova, Ocitavanje na 3-5cm. Alarmni tamper, Podrzava standardno PoE napajanje, Kontrola 2 brave, Detekcija pokreta, Internet protokol: SIP; P2P; IPv4; DNS; RTSP; RTP; TCP; UDP



VTO3211D-P (Jedan poziv)

IP Villa Spoljni pozivni tablo sa citacem kartica
2MP HD CMOS camera
Aluminum panel, IP65,IK08
Audio ulaz: Ugrađen mikrofون
Audio izlaz: Ugrađen spikerfon
Mrežni protokol: TCP/IP,
Vrsta instalacije- Nazidni,
Dimenzije: 182mm x 101mm x 30mm



VTO3211D-P2 (Dva poziva)

IP Villa Spoljni pozivni tablo sa citacem kartica
2MP HD CMOS camera
Aluminum panel, IP65,IK08
Audio ulaz: Ugrađen mikrofون
Audio izlaz: Ugrađen spikerfon
Bidirekciona komunikacija: Da
Tastatura: 2
Citac kartice: Da Mifare
Mrežni protokol: TCP/IP,
Vrsta instalacije- Nazidni,
Dimenzije: 182mm x 101mm x 30mm



VTO3211D-P4 (4 poziva)

IP Villa Spoljni pozivni tablo sa citacem kartica
2MP HD CMOS camera
Aluminum panel, IP65,IK08
Audio ulaz: Ugrađen mikrofون
Audio izlaz: Ugrađen spikerfon
Bidirekciona komunikacija: Da
Tastatura: 2
Citac kartice: Da Mifare
Mrežni protokol: TCP/IP,
Vrsta instalacije- Nazidni,
Dimenzije: 182mm x 101mm x 30mm



VTO2202F-P

IP Villa Door Station

2MP CMOS camera

Mechanical button

Night vision & voice indicator

PoE160° angle of view

Group call

Power supply by 2-wire

Aluminium alloy plate

IK07, IP65 (Apply silica gel to gaps between the device and the wall. Liquid sodium silicate is recommended. For details, see the quick start guide.)

Uzidna i nazidna mogućnost



VTO6221E-P Pozivna tabla

HD 1/2.9" 2MP CMOS kamera. Ekran 2.3" OLED. Radna temperatura

- 40°C~+60°C. Internet protokol TCP/IP. Support Dual-way Bidirectional talk. Citac Mifare Card (13.56MHz) .IK08, IP65. Kontrola za 1 vrata.



DEE1010B

Modul za proširenje kontrole pristupa

Pristojan izgled. Jednostavno povezivanje. Proširenje funkcije kontrole pristupa



VTNS1060A

Mrežno napajanje za IP interfone. (SWITCH). Povezivanje za maksimalno 6 unutrašnjih monitora sa CAT5E kablom.



VTOB101

Metalna uzidna dozna. Dozna za montažu B serija spoljašnjih pozivnih tabloa (DH-VTO1210B-X, DH-VTO1220B)



VTOB108
Metalna dozna za VTO2000A



VTOB111
Aluminijumska ugradna dozna za 2 modula



VTOB112
Aluminijumska ugradna dozna za 3 modula



VTOB113
Aluminijumska dozna za 2 modula



VTOB114
Aluminijumska dozna za 3 modula



VTOF002
Aluminijumski ram za 2 modula









VTOF003
Aluminijumski ram za 3 modula



VTM114
Aluminijumska ugradna dozna sa adapterom
Za poz.tablo VTO2202F-P



VTM115
Aluminijumska nadgradna dozna
Za poz.tablo VTO2202F-P

SLIKA	OPIS
Dahua citaci kartice	
	<p>ASM100 IC card (Mifare card) .Frekvencija 13.56MHz Dimenzije 105mm*75mm*20mm</p>
	<p>ASM100 -D Citac kartice na 125Khz.No driver installation, plug and play.Napajanje putem USB-a.</p>
Dahua kontrola pristupa	
	<p>ASI1201A-D RFID samostalni čitač sa tastaturom i displejom. 32-bitni CPU 16MB RAM. Podržava do 30.000 kartica. Memorija 150.000 događaja. Podržava kartica + šifra kombinacije. RJ45(10/100M) interfejs. Mrežni protokol: TCP/IP Napajanje: 9-15DC/200mA Protokol za povezivanje sa kontrolerom: RS485 Dimenzije: 150mm x 97mm x 16mm.</p>
	<p>ASR1200E-D RFID čitač otporan na vodu Viegand34 (26 opciono) bitova RS-485 protokola.125KHz (EM-ID).Vodootporni dizajn.Crvene, plave i zelene LED diode.Površinska montaža</p>
	<p>ASR1200E RFID čitač otporan na vodu Viegand34 (26 opciono) bitova RS-485 protokola.13,56 MHz (Mifare).Vodootporni dizajn.Crvene, plave i zelene LED diode.Površinska montaža.IP67</p>
	<p>ASR1100B RFID čitač otporan na vodu.Podrška RS485, Viegand34 protokol.13,56 MHz (Mifare)125KHz (EM-ID)Vodootporni dizajn.Indikatorska lampica sa crvenim, zelenim i plavim svetlom.Funkcija psa čuvara osigurava da se uređaj ne zaustavi.Površinska montaža</p>

**ASR1101A**

RFID čitač kartica.

Sensitive touch tastatura. RS485 interfejs. IP55 stepen zaštite. Radna temperatura -30°C-+60°C. Dimenzije 87mm×13mm×136mm. Napajanje 9V-15V DC/100mA

**ASR1101M**

RFID čitač kartica. Sensitive touch tastatura. RS485 interfejs. IK08 stepen zaštite. Radna temperatura -30°C-+60°C. Wiegand26/34 bits RS-485 protocol 13.56MHz(Mifare) 125KHz(EM-ID)

**ASI1201E**

čitač kartica. Sensitive touch tastatura.32-bitni CPU.Podrzava do 30.000 kartica. RS485 interfejs. IP66 stepen zaštite. Radna temperatura -30°C to +55°C. Dimenzije 62.0mm×142.0mm×23.0mm.Napajanje DC 9-15V/100mA

**ASR1201D**

Vodootporni RFID

čitač.**13.56MHz(Mifare)** Protokol RS485, Wiegand. Napajanje 5-16V DC / 100mA/ 300mA/ 800mA. Dimenzije 135mm x 47,5mm x 16mm.

**ASR1201D-D**

Vodootporni RFID

čitač.**125KHz(EM-ID)** Protokol RS485, Wiegand. Napajanje 5-16V DC / 100mA/ 300mA/ 800mA. Dimenzije 135mm x 47,5mm x 16mm.

**ASR1200D-D**

RFID čitač kartica. Sensitive touch tastatura.8-bitni CPU. RS485 interfejs. IP55 stepen zaštite.Daljina citanja kartice 2cm. Radna temperatura -30°C to +55°C. Dimenzije 135×47.5×16mm .Napajanje DC 9-15V/100mA

**ASI7213Y-V3**

Face Recognition 7 inch IPS display, resolution 1024×600.2MP wide-angle WDR lens.Unlock Mode Card/remote/password/face unlock and unlock through their combinations.Podrzava do 50000 korisnika.Napajanje DC 12V 2A

DAHUA KONTROLERI



ASC1202C-D

Komplet kontrolera za

dvoja vrata u metalnom kucistu sa napojnom jedinicom i punjacom. Za Wiegand/RS485 čitače. 32Bit sa 16MB RAM. Podržava do 100,000 kartica Memorija 150,000 događaja. Do 128 vremenskih rasporeda RJ45(10/100M) i RS485 interfejs. Radna temperatura -30°C+60°C. Dimenzije 280mm×114mm×320mm



ASC1204C-D

Mrežni kontroler za 4 vrata dvostrano u metalnom kućištu sa napojnom jedinicom i punjačem. Za Wiegand/RS485 čitače. 16MB RAM. Podržava do 100,000 kartica Memorija 150,000 događaja. Do 128 vremenskih rasporeda RJ45(10/100M) i RS485 interfejs. IP55 stepen zaštite Radna temperatura -30°C+60°C Dimenzije 280 x 320 x 114mm



ASC1204C-S

Mrežni kontroler za 4 vrata dvostrano u metalnom kućištu sa napojnom jedinicom i punjačem. Za Wiegand/RS485 čitače. 16MB RAM. Podržava do 100,000 kartica Memorija 150,000 događaja. Do 128 vremenskih rasporeda RJ45(10/100M) i RS485 interfejs. IP55 stepen zaštite Radna temperatura -30°C+60°C Dimenzije 280 x 320 x 114mm



ASC1208C-S

Mrežni kontroler za 8 vrata jednostrano u metalnom kućištu sa napojnom jedinicom i punjačem. Za Wiegand/RS485 čitače. 16MB RAM. Podržava do 100,000 kartica Memorija 150,000 događaja. Do 128 vremenskih rasporeda RJ45(10/100M) i RS485 interfejs. IP55 stepen zaštite Radna temperatura -30°C+60°C Dimenzije 266mm×87mm×290mm



ASC1202B-D

Mrežni kontroler za 4 čitača (2 vrata dvostrano). Za Wiegand / RS485 čitače. 32-bitni CPU. Podržava do 100,000 kartica. Memorija 300,000 događaja. Do 128 vremenskih rasporeda. RJ45(10/100M) i RS485 interfejs Radna temperatura -30°C+60°C Dimenzije 156mm x 98mm x 51mm



ASC1202B-S

Mrežni kontroler za dvoje vrata jednostrano. Za Wiegand/RS485 čitače. 32-bitni CPU. Podržava do 100,000 kartica. Do 128 vremenskih rasporeda. Napajanje DC 9-15V/500mA. Radna temperatura -30°C to +60°C. Dimenzije 156mm×51mm×98mm

**ASC1204B-S**

Mrežni kontroler za 4 vrata. Za Wiegand/RS485 čitače.32-bitni CPU.Podržava do 100,000 kartica.Do 128 vremenskih rasporeda.Napajanje DC 9-15V/500mA.Radna temperatura -30°C to +60°C.Dimenzije 210mm×51mm×106mm

**Dahua Tag ID-SM****Tag MIF 13.56MHz****Dahua Kartica ID-EM****Dahua Kartica Mifare****Dahua magneti I tasteri****ASF921**

Emergency break glass dugme.Tehnologija fotoelektrične kontrole za sprečavanje mehaničkih kvarova

Koristite vatrootporni materijal, prikladnu ugradnju

Normalno otvorene / zatvorene funkcije, fleksibilna aplikacija

500000 puta test na zamor i izdržljivost

Proizvodi dodatne opreme namenjeni projektu kontrole pristupa

**ASF900**

Plastično dugme za izlaz.Profesionalni dizajn kola, bez mehaničkih kvarova.Koristite vatrootporni materijal, prikladnu ugradnju.500.000 puta veći test i trajnost

Proizvodi dodatne opreme namenjeni projektu kontrole pristupa

**ASF280L**

Nosac elektromagnetne brave za 280kg



ASF280A

Magnetska brava sa jednim vratima.280KG Anti-pull

Ugrađeni uređaj za zaštitu od reverzne struje (MOV)

Aluminijumska školjka sa legurom visoke čvrstoće

Elektromagnetno usisavanje u potpunosti radi, nema mehaničkih oštećenja.Može se podesiti DC12V ili DC24V

Otporni na magnetni dizajn, otporni na habanje materijali

Tretman izolacije dvostrukog zaključavanja



ASF500L

Nosac elektromagnetne brave za 500kg



ASF500A

Magnetska brava sa jednim vratima.500KG Anti-pull

Ugrađeni uređaj za zaštitu od reverzne struje (MOV)

Aluminijumska školjka sa legurom visoke čvrstoće

Elektromagnetno usisavanje u potpunosti radi, nema mehaničkih oštećenja.Može se podesiti DC12V ili DC24V

Otporni na magnetni dizajn, otporni na habanje materijali

Tretman izolacije dvostrukog zaključavanja